

لیست قیمت مهر ۹۹

Starlight TC-C38LS Spec: I8/E/A/2.8-12mm

8MP **Starlight Face Capture** IR Bullet Camera
 1/2.8" 8Megapixel progressive CMOS
 Motorized Lens 2.8-12mm
 Up to 3840x2160@20fps
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR (120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
Support Face Capture
 Support Human/Vehicle Classification
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Crowed/Parking/Video Abnormal/Audio Abnormal/Heat Map)
 1/1 Audio In/Out, 2/1 Alarm In/Out
 Micro SD card 128GB
 Smart IR, IR Range: 80m
 IP67, PoE



Call

Starlight TC-C38JS Spec: I5/E/4mm

8MP **Starlight Face Capture** IR Bullet Camera
 1/2.8" 8Megapixel progressive CMOS
 Fixed Lens 4mm
 Up to 3840x2160@20fps
 Min. illumination Color: 0.01Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR(120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
Support Face Capture
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowed/Video Abnormal/Heat Map)
 Micro SD card 128GB
 Smart IR, IR Range: 50m
 Full Metal Housing
 IP67, PoE



Call

Starlight TC-C38KS Spec: I3/E/2.8mm

8MP **Starlight Face Capture** IR Dome Camera
 1/2.8" 8Megapixel progressive CMOS
 Fixed Lens 2.8mm
 Up to 3840x2160@20fps
 Min. illumination Color: 0.01Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR (120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
Support Face Capture
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowed/Video Abnormal/Audio Abnormal/Heat Map)
 Built-in Mic
 Micro SD card 128GB
 Smart IR, IR Range: 20m
 Full Metal Housing
 IP66, IK10, PoE



Call

Starlight TC-C35LS Spec: I8/E/A/2.8-12mm

5MP **Starlight Face Capture** IR Bullet Camera
 1/2.8" 5Megapixel progressive CMOS
 Motorized Lens 2.8-12mm
 Up to 2592x1944@20fps
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR (120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
 Support Human/Vehicle Classification
Support Face Capture
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowed/Video Abnormal/Audio Abnormal/Heat Map)
 1/1 Audio In/Out, 2/1 Alarm In/Out
 Micro SD card 128GB
 Smart IR, IR Range: 80m
 IP67, PoE



Call

Starlight TC-C35JS Spec: I5/E/4mm

5MP **Starlight Face Capture** IR Bullet Camera
 1/2.8" 5Megapixel progressive CMOS
 Fixed Lens 4mm
 Up to 2560x1920@20fps
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR (120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
Support Face Capture
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowed/Video Abnormal/Heat Map)
 Micro SD card 256GB
 Smart IR, IR Range: 50m
 Full Metal Housing
 IP67, PoE



Call

Starlight TC-C35MS Spec: I5/E/A/2.8-12mm

5MP **Starlight Face Capture** IR Dome Camera
 1/2.8" 5Megapixel progressive CMOS
 Motorized Lens 2.8-12mm
 Up to 2592x1944@20fps
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR(120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
 Support Human/Vehicle Classification
Support Face Capture
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowed/Video Abnormal/Audio Abnormal/Heat Map)
 Built-in Mic ,1/1 Audio In/Out, 2/1 Alarm In/Out
 Micro SD card 128GB
 Smart IR, IR Range: 50m
 IP66, IK10, PoE



Call



Starlight

TC-C35KS Spec: I3/E/2.8mm

5MP **Starlight Face Capture** mini IR Dome Camera
 1/2.8" 5Megapixel progressive CMOS
 Fixed Lens 2.8mm
 Up to 2592x1944@20fps
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/M-JPEG Triple-stream encoding
 WDR(120dB)/BLC/3D DNR/HLC/Corridor Format
 Support Smart Defog, ROI
Support Face Capture
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object Lost/Running/Loitering/Parking/Crowded/Video Abnormal/Audio Abnormal/Heat Map)
 Built-in Mic
 Micro SD card 256GB
 Smart IR, IR Range: 30m
 Full Metal Housing
 IP66, IK10, PoE



Call

TC-C34GN Spec: I5/E/C/4mm

4MP H.265 IR Bullet Camera
 1/2.7" 4Megapixel progressive CMOS
 Fixed Lens 4mm
 Up to 2560x1440@25fps
 Min. illumination Color: 0.02Lux
 S+265/H.265/H.264
 WDR (80dB)/BLC/3D DNR/HLC
 Support Smart Defog
 Smart IR, IR Range: 50m
 IP67, PoE



18,150,000

Starlight

TC-C34JS Spec: I5/E/C/4mm

4MP **Starlight** H.265 IR Bullet Camera
 1/2.7" 4Megapixel progressive CMOS
 Fixed Lens 4mm
 Up to 2560x1440@25fps
 Min. illumination Color: 0.005Lux
 S+265/H.265/H.264
 WDR(80dB)/BLC/3D DNR/HLC
 Support Smart Defog
 Full Metal Housing
 Smart IR, IR Range: 50m
 IP67, PoE



Call

Starlight

TC-C34HS Spec : I3/E/C/M/2.8mm

4MP **Starlight** H.265 IR Turret Camera
 1/2.7" 4Megapixel progressive CMOS
 Fixed Lens 2.8mm
 Up to 2560x1440@25fps
 Min. illumination Color: 0.005Lux
 S+265/H.265/H.264
 WDR(80dB)/BLC/3D DNR/HLC
 Built-in Mic
 Support Smart Defog
 Full Metal Housing
 Smart IR, IR Range: 30m
 IP66, PoE



Call

TC-C34HN Spec: I3/E/C/2.8mm

4MP H.265 IR Turret Camera
 1/2.7" 4Megapixel progressive CMOS
 Fixed Lens 2.8mm
 Up to 2560x1440@25fps
 Min. illumination Color: 0.02Lux
 S+265/H.265/H.264
 WDR(80dB)/BLC/3D DNR/HLC
 Built-in Mic
 Support Smart Defog
 Metal+Plastic Housing
 Smart IR, IR Range: 30m
 IP66, PoE



18,150,000

Super Starlight

TC-C32GP Spec : I5/E/C/4mm

2MP **Super Starlight** IR Bullet Camera
 1/2.8" 2MP progressive scan CMOS
 Min. illumination Color: 0.0008Lux
 4mm fixed lens
 1920x1080@25 fps
 S+265/H.265/H.264 dual-stream encoding
 WDR(80dB), Day/Night (ICR), BLC, 3D DNR, HLC
 Smart Defog
 Metal+Plastic Housing
 Smart IR, IR Range: 50m
 PoE, IP67



19.500.000



TC-C32GN Spec: I5/E/4mm

2MP H.265 IR Bullet Camera
 1/2.9" 2MP progressive scan CMOS
 Min. illumination Color: 0.02Lux
 4mm fixed lens
 1920x1080@25 fps
 S+265/H.265/H.264 dual-stream encoding
 WDR (80dB), Day/Night (ICR), BLC, 3D DNR, HLC
 Smart Defog
 Smart IR, IR Range: 50m
 PoE, IP67



12.500.000

TC-C32HN Spec: I3/E/2.8mm

2MP H.265 IR Turret Camera
 1/2.9" 2MP progressive scan CMOS
 Min. illumination Color: 0.02Lux
 2.8mm fixed lens
 1920x1080@25 fps
 S+265/H.265/H.264 dual-stream encoding
 WDR (80dB), Day/Night (ICR), BLC, 3D DNR, HLC
 Smart Defog
 Metal+Plastic Housing
 Smart IR, IR Range: 30m
 PoE, IP66



12.500.000

TC-C32JN Spec: I5/E/4mm

2MP H.265 IR Bullet Camera
 1/2.9" 2MP progressive scan CMOS
 Min. illumination Color: 0.02Lux
 4mm fixed lens
 1920x1080@25 fps
 S+265/H.265/H.264 dual-stream encoding
 WDR (80dB), Day/Night (ICR), BLC, 3D DNR, HLC
 Smart Defog
 Smart IR, IR Range: 50m
 PoE, IP67



Call

TC-C32KN Spec: I2/E/2.8mm

2MP Vandal Proof Mini IR Dome Camera
 1/2.7" 2Megapixel progressive CMOS
 Min. illumination Color: 0.02Lux
 2.8mm Fixed lens
 25fps@2M(1920X1080)
 S+265/H.264/MJPEG Triple-stream encoding
 WDR (80dB), Day/Night (ICR), 3DNR, HLC, BLC
 Smart Defog, ROI
 VCA (Tripwire/Double
 Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Video
 Abnormal Detection/People counting/ Facial
 Detection)
 Built in Mic, 1/0 Audio In/Out, Micro SD card
 128GB
 Max IR LEDs Length 20m, Smart IR
 Cable Free Design
 IP66, IK10, PoE



Call

Starlight

TC-NCL514S

5MP Starlight IR Bullet Camera (4mm)
 1/2.8" 5Megapixel progressive CMOS
 4mm fixed lens
 2560x1920@20fps
 S+265/H.265/H.264 dual-stream encoding
 Min. illumination Color: 0.002Lux
 WDR (80dB), 3DNR, Day/Night (ICR), HLC, BLC,
 Corridor Format
 Smart Defog, ROI
 VCA (Tripwire/Double
 Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Video
 Abnormal Detection/ Face Detection/
 Demographics)
 Max IR LEDs Length 50m, Smart IR
 IP67, PoE



27.500.000

Starlight

TC-NCL522S

5MP Starlight IR Turret Camera
 1/2.8" 5Megapixel progressive CMOS
 2.8mm Fixed lens
 2560x1920@20fps
 S+265/H.265/H.264 dual-stream encoding
 Min. illumination Color: 0.002Lux
 WDR (80dB), Day/Night (ICR), 3D DNR, BLC, HLC
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Crowd /Video
 Abnormal Detection/ Face Detection/
 Demographics)
 Smart Defog, ROI
 Metal+Plastic Housing
 Max IR LEDs Length 30m, Smart IR
 IP66, PoE



27.500.000



Starlight

TC-NC514S

5MP **Starlight** IR Bullet Camera
 1/2.8" 5Megapixel progressive CMOS
 4mm fixed lens
 2560×1920@20fps
 S+265/H.264/M-JPEG triple-stream encoding
 Min. illumination Color: 0.002Lux
 WDR (120db), Day/Night (ICR), BLC/3D
 DNR/HLC/Corridor Format
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Video
 Abnormal)
 Support Smart Defog, ROI
 Micro SD card 128GB
 Metal Housing
 Max IR LEDs Length 50m, Smart IR
 PoE, IP67



Call

Starlight

TC-NC552S

5MP **Starlight** IR Dome Camera
 1/2.8" 5Megapixel progressive CMOS
 2.8mm Fixed lens
 2560×1920@20fps
 Min. illumination Color: 0.002Lux
 S+265/H.264/M-JPEG triple-stream encoding
 WDR (120dB), Day/Night (ICR), 3DNR, BLC, HLC, Corridor
 Format
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Audio
 Abnormal/Video Abnormal)
 Smart Defog, ROI
 Built in Mic, 1/0 Audio In/Out
 Micro SD card 128GB
 Metal Housing
 Max IR LEDs Length 20m, Smart IR
 Cable Free Design
 IP66, IK10, PoE



Call

TC-NC43M

4MP H.265 Motorized IR Bullet Camera
 1/3" 4Megapixel progressive CMOS
 Motorized Lens 2.8-12mm
 Up to 2560x1440@25fps
 Min. illumination Color: 0.02Lux
 S+265/H.265/H.264/M-JPEG triple-stream
 encoding
 WDR (120dB), BLC, 3D DNR, HLC, Corridor Format
 Smart Defog, ROI
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Audio
 Abnormal/Video Abnormal)
 1/1 Audio in/Out, 2/1 Audio in/Out
 RS485, USB, Micro SD card 128GB
 Smart IR, IR Range: 50m
 IP67, PoE



Call

TC-NC44M

4MP H.265 Motorized IR Dome Camera
 1/3" 4Megapixel progressive CMOS
 Motorized Lens 2.8-12mm
 Up to 2560x1440@25fps
 Min. illumination Color: 0.02Lux
 S+265/H.265/H.264/M-JPEG Triple-stream
 encoding
 WDR (120dB), Day/Night (ICR), BLC, 3D DNR, HLC,
 Corridor Format
 Smart Defog, ROI
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Audio
 Abnormal/Video Abnormal)
 Smart Defog, ROI
 Built in Mic
 1/1CH Audio In/Out, 2/1 Alarm In/Out
 Micro SD card 128GB
 Smart IR, IR Range: 30m
 IP66, IK10, PoE



Call

Super Starlight

TC-NC294XG + Bracket

2MP Super Starlight EXIR Bullet Camera
 1/2.7" 2Megapixel progressive CMOS
 4mm fixed lens, Angle of View:90°
 25fps@2M (1920*1080)
 S+265/H.264/MJPEG Encoding
 Starlight Ultra Low Light 0.0004 lux, IR Free Design
 WDR (140dB), Day/Night (ICR), 3DNR, HLC
 Smart Defog, ROI
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Audio Abnormal/Video Abnormal)
 1/1 Audio In, 1 Alarm In
 Micro SD card 128GB
 IP67, PoE



Call



Starlight

TC-NH3204IE

2MP 4x Starlight Mini EW IR POE PTZ
 1/2.8" 2Megapixel CMOS
 S+265/H.264/MJPEG Triple-streams encoding
 Max.25fps@2MP(1920*1080)
 2.8mm~12mm 4x optical zoom
 Starlight Ultra Low Light 0.002lux
 WDR (140dB), ICR, 3D-DNR, HLC, BLC
 Support Defog, ROI
 *Early Warning (EW)
 IR LED + White Light + Speaker
 VCA (Tripwire/Double Tripwire/Perimeter/Object Abandon/Object
 Lost/Running/Loitering/Parking/Early Warning/Crowd/Audio
 Abnormal/Video Abnormal)
 Up to 500 presets,8 Cruise,8 pattern
 Built-In Mic, Built-In Speaker
 Alarm 2/1 in/out, Audio 1/0 in/out
 Micro SD card 128GB
 IR Distance up to 50m
 IP65, PoE



Call

Super Starlight

TC-A3563 Spec:44X/I/A

5MP 44x Super Starlight IR Face Capture AEW PTZ
 Camera
 1/1.8" 5Megapixel CMOS
 Up to 3072x1728@20fps
 Min. illumination Color: 0.0008Lux
 S+265/H.265/H.264/MJPEG Triple-streams
 encoding
 6mm~264mm 44x optical zoom
 WDR (140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
 Smart Defog, ROI
 Auto-Tracking Early Warning (AEW)
 Support Human/Vehicle Classification
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Face
 Detection/People Counting/Crowded/Audio
 Abnormal/Video Abnormal/On Duty
 Detection/Heatmap/Safety Helmet Detection)
 500 presets,16 Cruise (32 preset per cruise),8
 pattern
 8/2 Alarm in/out, 1/1 Audio in/out
 Micro SD card 128GB
 Built-in Speaker, Wiper, RS-485
 IR Distance up to 180m
 IP66



Call

Starlight

TC-H326S Spec:33X/I/E/A

2MP 33x Starlight IR POE PTZ Camera
 1/2.8" 2Megapixel CMOS
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/MJPEG Triple-streams encoding
 Up to 1920X1080@60fps
 4.6mm~152mm 33x optical zoom
 WDR (140dB), Dual IR Cut Filter, 3D-DNR, HLC, BLC
 Smart Defog, ROI
Support Auto Tracking
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Audio Abnormal/Video
 Abnormal/Heatmap)
 Up to 500 presets,16 Cruise,8 pattern
 1/1 Alarm in/out, 1/1 Audio in/out
 Micro SD card 128GB
 Smart IR, IR Range: 150m
 IP66



Call

TC-H324S Spec25X/I/E

2MP 25x Starlight IR PTZ Camera
 1/2.8" 2Megapixel CMOS
 Up to 1920X1080@25fps
 Min. illumination Color: 0.002Lux
 S+265/H.265/H.264/MJPEG Triple-streams
 encoding
 4.8mm~120mm 25x optical zoom
 WDR (140dB), Dual IR Cut Filter, 3D-DNR, HLC,
 BLC
 Smart Defog, ROI
 VCA (Tripwire, Double Tripwire, Perimeter,
 Object Abandon, Object Lost)
 500 presets,16 Cruise (32 preset per cruise),8
 pattern
 1/1 Alarm in/out, 1/1 Audio in/out
 Micro SD card 128GB
 Built-in Heater
 IR Distance up to 150m
 IP66, PoE+



97,000,000

Starlight

TC-NH6220IE-CP

2MP 20x Starlight IR POE PTZ Camera
 1/2.8" 2Megapixel CMOS
 S+265/H.264/MJPEG Triple-streams encoding
 Up to 1920X1080@25fps
 5.2mm~98mm 20x optical zoom
 Min. illumination Color: 0.002Lux
 WDR (140dB), ICR, 3D-DNR, HLC, BLC
 Smart Defog
 VCA (Tripwire/Double Tripwire/Perimeter/Object
 Abandon/Object
 Lost/Running/Loitering/Parking/Crowd/Audio
 Abnormal/Video Abnormal)
 Up to 500 presets,8 Cruise,8 pattern
 Built in Mic
 1/1 Alarm in/out
 1/1 Audio in/out
 Micro SD card 128GB
 Smart IR, IR Range: 120m
 IP66, PoE+



137.000.000



TC-R3105 Spec: I/B/V2.0

5CH 1HDD 1U NVR
 5 IP camera input + 2 CH expansion = 7CH
 S+265/H.265/H.264 video formats
 Max 40/40 Mbps incoming/Outgoing bandwidth
 Up to 5M Resolution Recording
 VCA detection alarm is supported
 HDMI and VGA simultaneous output
 HDMI Video output at up to 1080P (1920 × 1080)
 1 SATA interface, up to 10TB for 1 HDD
 1CH Audio output
 2 USB Ports
 1*10/100 Mbps Network Card
 P2P support



18,600,000

TC-R3110 Spec: I/B/V2.0

10CH 1HDD 1U NVR
 10 channel IP camera input
 S+265/H.265/H.264 video formats
 Max 40/40 Mbps incoming/Outgoing bandwidth
 Up to 5MP Resolution Recording
 VCA detection alarm is supported
 HDMI (1080P)/VGA simultaneous video output
 Support 1 SATA HDD up to 10TB
 1CH Audio output
 2 USB Ports
 1*10/100 Mbps Network Card
 P2P support



21,400,000

TC-R3210 Spec: I/F

10CH 2HDD 10ch Face Recognition NVR
 10 IP camera input
 S+265/H.265/H.264 video formats
 Max 80/80 Mbps incoming/Outgoing bandwidth
 Up to 6MP Resolution Recording
 Support Face Recognition: Face Picture Search/capturing pictures and typing in the library/encryption library management/face alarm information linkage
 Base Libraries:32, Face pictures:10,000
 Recognition with Face Capture camera: 5CH
 Recognition with Normal camera: 1CH
 VCA detection alarm is supported
 HDMI and VGA simultaneous output(1080P)
 2 SATA interfaces, up to 10TB for each HDD
 Two-way Audio Input 1-ch
 1CH Audio output
 0/1 Alarm In/Out
 2 USB Ports
 1*10/100 Mbps Network Card
 P2P support



Call

TC-R3120 Spec: I/B/V2.0

20CH 1HDD 1U NVR
 20 channel IP camera input
 S+265/H.265/H.264 video formats
 Max 80/80 Mbps incoming/Outgoing bandwidth
 Up to 8MP Resolution for Preview
 VCA detection alarm is supported
 HDMI(4K)/VGA simultaneous video output
 Support 1 SATA HDD up to 10TB
 1CH Audio output
 2 USB Ports
 1*10/100 Mbps Network Card
 P2P support



27,500,000

TC-R3220

20CH 2HDD 1U NVR
 20 channel IP camera input
 S+265/H.265/H.264 video formats
 Max 80/80 Mbps incoming/Outgoing bandwidth
 Up to 8MP Resolution for Preview
 VCA detection alarm is supported
 HDMI and VGA simultaneous output
 1*HDMI(4K)/1*VGA video output
 Support 2 SATA HDD (10TB each SATA)
 2*USB Ports
 Two-way Audio Input 1-ch
 1CH Audio output
 0/1 Alarm In/Out
 1*10/100 Mbps Network Card
 P2P support



40.000.000



TC-R3420

20CH 4HDD 1.5U NVR
 20 channel IP camera input
 S+265/H.264 video formats
 Max 400/200 Mbps incoming/Outgoing bandwidth
 Up to 4K Resolution for Preview
 VCA detection alarm is supported
 HDMI/VGA simultaneous video output
 Max output Resolution 4K
 Support 4 SATA HDD (10TB each SATA)
 2 USB Ports, 16/4 Alarm In/Out
 2*RS-485, 1*RS-232
 Two-way Audio Input 1-ch
 1CH Audio output
 2*10/100/1000 Mbps Network Card
 P2P support



Call

TC-R3440 Spec: I/B/N

40CH 4HDD 1.5U NVR
 40 channel IP camera input
 S+265/H.265/H.264 video formats
 Max 400/200 Mbps incoming/Outgoing bandwidth
 Up to 12MP Resolution for Preview
 VCA detection alarm is supported
 HDMI and VGA independent outputs
 1*HDMI(4K)/1*VGA video output
 Support 4 SATA HDD(10TB each SATA)
 2 USB Ports, 1*RS-485, 1*RS-232
 Two-way Audio Input 1-ch
 1CH Audio output
 16/4 Alarm In/Out
 2*10/100/1000 Mbps Network Card
 P2P support



Call

TC-R3840 Spec: I/B/N

40CH 8HDD 2U NVR
 40 channel IP camera input
 S+265/H.265/H.264 video formats
 Max 400/200 Mbps incoming/Outgoing bandwidth
 Max 12MP Resolution for Preview
 VCA detection alarm is supported
 HDMI and VGA independent outputs
 2*HDMI (4K)/2*VGA video output
 Support N+M Hot Standby
 Support ANR
 8*SATA HDD up to 10TB for each HDD
 1*e-SATA
 Support Raid JBOD, RAID0/1/5/6/10
 3*USB Ports
 Two-way Audio Input 1-ch
 1x3.5mm, 1xBNC Audio output
 16/4 Alarm In/Out
 2*RS-485, 1*RS-232
 2*10/100/1000 Mbps Network Card
 P2P support



Call

TC-R3880 Spec: I/B/N

80CH 8HDD 2U NVR
 80 channel IP camera input
 S+265/H.265/H.264 video formats
 Max 400/200 Mbps incoming/Outgoing bandwidth
 Max 12MP Resolution for Preview
 VCA detection alarm is supported
 HDMI and VGA independent outputs
 2*HDMI(4K)/2*VGA video output
 Support N+M Hot Standby
 Support ANR
 8*SATA HDD up to 10TB for each HDD
 1*e-SATA
 Support Raid JBOD, RAID0/1/5/6/10
 3*USB Ports
 Two-way Audio Input 1-ch
 1x3.5mm, 1xBNC Audio output
 16/4 Alarm In/Out
 2*RS-485, 1*RS-232
 2*10/100/1000 Mbps Network Card
 P2P support



Call

