IP Price List

آذر و دی ۱۴۰۰

لیست قیمت مصرف کننده

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
1	PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9” 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9” 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
2	PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9” 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9” 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
3	PFW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8” 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function|Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
4	PFW8601-A180	3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8” 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens, Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function|Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
5	PDBW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8” 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function|Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
6	ITC237-PW1B-IRZ	**دوربین ANPR با قابلیت تشخیص پلاک ،مناسب برای ورودی های پارکینگ** 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database,1 ch relay out to control the barrier performance for outdoor applications· 1/2.8” 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE		128,000,000
7	IPC5831EP-ZE	1/2.5” 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) 2.7mm ~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE (Tripwire|Intrusion|Object Abandoned/Missing|Face)		97,000,000
8	HFW4831EP-SE	1/2.5” 8Megapixel progressive scan STARVIS™ CMOS H.265+&H.265&H.264&MJPEG triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) Minimum Illumination 0.06Lux/F1.6(Color,1/3s,30IRE)/0.3Lux/F1.6(Color,1/30s,30IRE)/0Lux/F1.6(IR on) WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI 4mm & 2.8mm fixed lens, Max. IR LEDs Length 40m Face Detection, Tripwire, Intrusion, Object Abandoned / Missing Micro SD card memory , 128 GB, IP67, PoE Smart Detection (Tripwire|Intrusion | Scene Change | Face)		57,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
9	IPC-HFW2831T-ZAS-S2 STARLIGHT	NEW 8MP Lite IR Vari-focal Bullet Network Camera 8MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.5 high image definition 8MP@15fps & 4MP@25/30fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+, (MJPEG in Sub Stream) IVS Intrusion, Tripwire Micro SD 256GB, 1ch Audio I/O, 1ch Alarm I/O WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V. PoE. IP67. 4 IR LEDs 60m Distance. Onvif Profile S/G/T		67,000,000
10	HFW2831T-ZS STARLIGHT	8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm–13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire|Intrusion)		65,500,000
11	HFW5631EP-ZHE STARLIGHT ePoE	6MP WDR IR Bullet Network Camera 1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 Triple-stream encoding 20fps@6M(3072×2048),25/30fps@4M(2688×1520) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 7mm~35mm(5x zoom) Motorized lens Max. IR LEDs Length 100m, Micro SD card memory , 128 GB 2/1 Alarm in/out, 1/1 audio in/out, IP67, IK10, PoE (Tripwire|Intrusion | Object Abandoned | Missing| Face)		95,000,000
12	HFW4631EP-SE STARLIGHT Ambarella ePoE	1/2.9" 6Megapixel progressive scan STARVISTM CMOS H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens, Max. IR LEDs Length 40m Micro SD card memory , 128 GB, IP67, PoE (Tripwire|Intrusion |Object Abandoned/Missing| Face)		49,000,000
13	HFW2531TP-ZS STARLIGHT	1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB, Max IR LEDs Length 60m ,Smart IR IP67, PoE, Smart Detection (Tripwire|Intrusion)		58,300,000
14	HFW5442EP-ZE-0832 Ambarella ePoE WizMind	4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688×1520), 50/60fps@2Mp(1920 × 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lenz, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE		100,000,000
15	HFW5431EP-ZE Ambarella ePoE	4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25/30fps@4Mp(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 IP67, IK10, PoE, (Tripwire|Intrusion | Object Abandoned / Missing | Face)		81,000,000
16	IPC-HFW5241E-Z5E STARLIGHT WizMind ePoE	NEW 2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8" Progressive STARVIS™ CMOS low illuminance 0.0015 Lux@F1.3 high image definition 2MP@25/30fps 7-35mm Motorized Lens SMART H.264+/H.265+ IVS: Tripwire; intrusion; fast moving (with accurate classification of vehicle and human); loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS, Defog, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T		83,500,000
17	HFW5231EP-Z12E STARLIGHT Ambarella ePoE	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 5.3mm ~ 64mm 12x zoom lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card up to 128 GB, Max. IR LEDs Length 200m , Smart IR IP67, IK10, PoE, (Tripwire|Intrusion|Object Abandoned/Missing|Face)		83,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
18	HFW5231EP-ZE STARLIGHT Ambarella PoE	1/2.8” 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 13.5mm motorized lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card memory , 128 GB, Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE, Smart Detection (Tripwire|Intrusion|Object Abandoned/Missing|Face)		78,000,000
19	DH-IPC-HFW4431EP-Z-S4	4MP WDR IR Bullet Network Camera 1/3” 4Megapixel progressive CMOS 2.7mm~13.5mm motorized lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Facedetection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2/1 Alarm in/out, 1/1 audio in/out Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, IK10, PoE		70,000,000
20	DH-IPC-HFW4431TP-S-S4	4MP WDR IR Mini Bullet Network Camera 1/3” 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE		38,300,000
21	HFW3441TP-ZS-27135 STARLIGHT WizSense	4MP IR Vari-focal Bullet WizSense Network Camera 1/3”4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm–13.5 mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE		62,000,000
22	IPC-HFW2439SP-SA-LED NEW Full-Color	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T		30,500,000
23	HFW2431TP-ZS-S2 STARLIGHT	4MP WDR IR Bullet Network Camera 1/3” 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5, 2.7–13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire|Intrusion) Micro SD memory 256 GB, max IR distance:60 m, Smart IR, IP67, PoE		53,500,000
24	IPC-HFW1431S1-S4-S5 NEW	4MP Entry IR Fixed-focal Bullet Netwok Camera 4MP, 1/3” Progressive CMOS low illuminance 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart H.265+/H.264+ WDR(120db), RoI, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)		22,300,000
25	HFW1431SP-0360B-S4	4MP Entry IR Fixed-focal Bullet Netwok Camera 1/3”4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.03 Lux@F2.0, 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR, IP67, PoE		24,500,000
26	IPC-HFW3541T-ZS STARLIGHT WizSense	5MP IR Vari-focal Bullet WizSense Network Camera 5MP, 1/2.7” Progressive CMOS 0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on) high image definition 5MP@20fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ 3 Streams IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T		69,000,000
27	IPC-HFW2531TP-AS-S2 STARLIGHT	5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.6 high image definition 5MP@20fps, 3.6mm fixed Lens SMART H.264+/H.265+, IVS Intrusion/Tripwire 1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T		42,800,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
28	HFW2431SP-S-S2 STARLIGHT	4MP WDR IR Bullet Network Camera 1/3” 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire|Intrusion) Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE		27,800,000
29	HFW2231SP-S-S2 STARLIGHT	2MP WDR IR Bullet Network Camera, starlight 1/2.8” 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		25,300,000
30	HFW2230SP-S STARLIGHT	2MP IR Bullet Network Camera 1/2.7” CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire|Intrusion)		22,600,000
31	NEW IPC-HFW2231T-ZS-S2 STARLIGHT	2MP Lite IR Vari-focal Bullet Network Camera 2MP, 1/2.8” Progressive CMOS, low illuminance 0.002 Lux@F1.5 high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card 256 GB WDR(120db), RoI, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T		48,800,000
32	DH-IPC-HFW1239S1-LED-S5 Full-color	2MP Lite Full-color Fixed-focal Bullet Netwok Camera 2MP, 1/2.8” Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T		18,900,000
33	HFW1230SP-S4-S5	2MP Entry IR Fixed-focal Bullet Netwok Camera 1/2.7” 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE		18,800,000
34	STARLIGHT HDBW5831EP-ZE Ambarella PoE	1/2.5” 8Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3M(2304×1296) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 12mm motorized lens 1/1 Audio in/Out, 1/1 Alarm In/Out Micro SD card memory , 128 GB Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE+, (Tripwire|Intrusion|Object Abandoned/Missing|Face)		95,000,000
35	HDBW5431EP-Z-H	1/3” 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 &MJPEG triple-stream encoding Max 20fps@4Mp(2560×1440),25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens, Max. IR LEDs Length 50m IP67,IK10, PoE, Micro SD card memory , 128 GB Audio in/Out, Alarm In/Out Smart Detection (Tripwire|Intrusion | Scene Change | Face)		81,000,000
36	STARLIGHT HDBW4831EP-ASE PoE	1/2.5” 4K progressive scan Starvis CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 30m Alarm in/out, Audio in/out Micro SD card memory , 128 GB, IP67,IK10, PoE Smart Detection (Tripwire|Intrusion|Scene Change|Object Abandoned/Missing |Face)		57,000,000
37	HDW4831EMP-ASE Ambarella PoE	1/2.5” 4K progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 50m Built-in Mic , Micro SD card memory , 128 GB IP67,PoE, (Tripwire|Intrusion|Scene Change|Object Abandoned/Missing |Face)		57,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
38	HDW4631EM-ASE Eco-Savvy Lite Ambarella ePoE	1/2.9” 6Megapixel progressive scan STARVISTM CMOS H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Built-in Mic Max. IR LEDs Length 50m, Smart IR Micro SD card memory , 128 GB, IP67, PoE (Tripwire|Intrusion |Object Abandoned/Missing| Face)		49,000,000
39	HDW4431EMP-AS-S4	4MP IR Eyeball Network Camera 1/3” 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE		34,800,000
	HDW3441TMP-AS-0280B	4MP IR Fixed focal Eyeball WizSense Network Camera 1/3”4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic Micro SD memory 256GB		36,800,000
40	HDBW2531RP-ZAS	1/2.7” 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Mirco SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67,IK10, PoE		57,300,000
41	IPC-HDBW2531E-S-S2	NEW 5MP Lite IR Fixed-focal Dome Network Camera 5MP, 1/2.7” Progressive CMOS Min. Illumination 0.008 Lux @ F1.6 Max 5MP@20fps SMART H.264+/H.265+ IVS: Intrusion, tripwire Mirco SD card 256GB WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI max IR distance: 30m, 12V DC, PoE, IP67,IK10		30,300,000
42	IPC-HDW2439TP-AS-LED	NEW 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T		30,500,000
43	HDBW2431RP-ZAS-S2	4MP WDR IR Dome Network Camera 1/3” 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7–13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire|Intrusion) Micro SD memory 256 GB, Built in Mic 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE		53,000,000
44	HDBW2431EP-S-S2	4MP IR Mini Dome Network Camera 1/3” 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 2.8mm/3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire|Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE		27,800,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
45	HDW2431TMP-AS-S2 STARLIGHT	4MP WDR IR Eyeball Network Camera, Starlight 1/3” 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire|Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE		**28,800,000**
46	HDW1431T1P-0280B-S4-S5	4MP Entry IR Fixed-focal Eyeball Netwok Camera 1/3”4Megapixel progressive CMOS 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE		**22,300,000**
47	HDW2231TMP-AS-S2 STARLIGHT	2MP WDR IR Eyeball Network Camera, Starlight 1/2.8” 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		**26,300,000**
48	IPC-HDW2231TP-AS-S2 STARLIGHT	NEW 2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8” Progressive CMOS low illuminance 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		**25,300,000**
49	IPC-HDW2230T-AS-S2 STARLIGHT	NEW 2MP IR Eyeball Network Camera 2MP, 1/2.7” Progressive CMOS low illuminance 0.005 Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		**22,600,000**
50	IPC-HDBW2230E-S-S2 STARLIGHT	NEW 2MP Lite IR Fixed-focal Dome Network Camera 2MP, 1/2.7” Progressive CMOS low illuminance 0.005` Lux @F1.6 high image definition 2MP@25/30fps 2.8mm Fixed Lens SMART H.264+/H.265+ IVS Tripwire; intrusion Micro SD 256GB DWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T		**22,600,000**
51	DH-IPC-HDW1239T1-LED-S5 STARLIGHT Full-color	NEW 2MP Lite Full-color Fixed-focal Eyeball Netwok Camera 2MP, 1/2.8” Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T		**18,900,000**
52	HDW1230T1P-S4	2MP Entry IR Fixed-Focal Eyeball Netwok Camera 1/2.7” 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR IP67, PoE		**17,400,000**
53	HDBW1230EP-S4-S5	1/2.7” 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE		**19,000,000**

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
54	DH-SD29204T-GN	1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire|Intrusion | Scene Change | Face| Abandoned-Missing Object)		53,000,000
55	DH-SD1A203T-GN STARLIGHT	1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire|Intrusion|Abandoned/Missing|Face Detection)		56,000,000
56	DH-SD6CE230U-HNI STARLIGHT	1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10		250,000,000
57	SD6CE225U-HNI STARLIGHT	1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.8mm~120mm 25x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC Support Defog, ROI, EIS, Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 Alarm 7/2 in/out, Audio 1/1 in/out IR Distance up to 200m, PoE+, IP67, IK10		167,000,000
58	DH-SD6CE245U-HNI STARLIGHT	2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10		Call
59	SD49225XA-HNR STARLIGHT	2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+		145,000,000
60	SD49225T-HN-S2 STARLIGHT	1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6)B/W:(0.0005Lux@F1.6) Max. 25/30fps@1080P, 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR,BLC, HLC, AWB, AGC, ROI Support Defog IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, 1/1 Audio in/out Support PoE+, IR Distance up to 100m, IP66		135,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
61	SD65F230F-HNI Super STARLIGHT	1/1.9” 2MP CMOS Sensor**(Super Starlight)** H.264 / MJPEG Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P 6mm~180mm Powerful 30x optical zoom Max 300°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out, Audio 1/1 in/out, 1 video output RS485, IR Distance up to 100m, Support PoE+, IP66,IK10		**Call**
62	DH-SD59432XA-HNR STARLIGHT WizSense	4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Min. Illumination:Color(0.005Lux@F1.3)B/W(0.0005Lux@F1.3) Max. 25/30fps@4M 4.9 mm–156 mm Focal Length, 32x optical zoom Deep-learning-based auto tracking and perimeter protection(Recognition of human and vehicle) IVS(Tripwire, intrusion, Object abandoned/missing, Face Detection) WDR(120dB), Day/Night(ICR), Ultra DNR, AWB, AGC, BLC, HLC Support Defog and EIS , RoI Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66		**295,000,000**
63	SD59225U-HNI STARLIGHT	2MP 25x **Starlight** IR PTZ Network Camera 1/2.8” Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.8mm~120mm 25x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66,OSD		**157,000,000**
64	SD59230U-HNI STARLIGHT	2MP 30x **Starlight** IR PTZ Network Camera 1/2.8” Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.5mm~135mm 30x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66,OSD		**231,000,000**
65	SD59430U-HNI	1/3” CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592×1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire|Intrusion | Scene Change | Face| Anondoned-Missing Object)		**257,000,000**
66	SD5A432XA-HNR STARLIGHT WizSense	NEW 4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm–156 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, RoI,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient protection		**290,000,000**
67	SD5A445XA-HNR AI STARLIGHT WizSense	NEW 4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on) 3.95 mm–177.7 mm Powerful 45x optical zoom Max. Aperture F1.6–F4.95 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, RoI,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection		**350,000,000**

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
68	SD6CE445XA-HNR	NEW 4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8” 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on) 3.95 mm–177.75 mm Powerful 45x optical zoom Max. Aperture F1.6–F4.95 Pan/Tilt Range Pan: 0°–360° endless; Tilt: -20°–90°,auto flip 180° Preset Speed Pan: 300° /s; Tilt: 200° /s WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, RoI, EIS, Defog Deep-learning-based auto tracking and perimeter protection Face detection, SMD Plus, Tripwire, Intrusion. Human/Vehicle/Motor-non Motor Vehicle Detection Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&G&T IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10		380,000,000
69	DHI-NVR1104HS-S3/H	NEW 4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity : 1–ch@8MP(30FPS) or 1–ch@5MP(30FPS) or 2–ch@4MP(30FPS) or 2–ch@3MP(30FPS) or 4–ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ–45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)		19,900,000
70	NVR2104HS-4KS2	4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		22,800,000
71	NVR2104HS-P-4KS2	4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support		30,000,000
72	DHI-NVR1108HS-S3/H	NEW 8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity : 1–ch@8MP(30FPS) or 1–ch@5MP(30FPS) or 2–ch@4MP(30FPS) or 2–ch@3MP(30FPS) or 4–ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ–45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)		23,100,000
73	NVR2108HS-4KS2	8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		28,000,000
74	NVR2108HS-8P-4KS2	8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support		40,500,000
75	NVR2108HS-I	NEW 8 Channel 12MP WizSense NVR 1/4/8 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled : 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ–45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)		35,000,000
76	NVR4108HS-4KS2	8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		30,000,000
77	DHI-NVR2216-4KS2	NEW 16 Channel 4K Lite H.265 NVR 1/4 Live & Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ–45 port (1000Mbps), P2P Support		42,800,000

ردیف	مدل		مشخصات فنی	تصویر	قیمت (ریال)
78	NVR2116HS-I	NEW 12MP WizSense AI	16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ–45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)		42,000,000
79	DHI-NVR2216-I	NEW 12MP WizSense AI	16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ–45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)		59,300,000
80	NVR4116HS-4KS2	NEW 4K AI	16 Channel Compact 1U 4K&H.265 Lite Network Video Recorder Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map target classification (human, vehicle) HDMI(4K)/VGA simultaneous video output 1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 port Audio I/O 1/1 for Two Way Talk Only 100 Mbps Network Card, P2P support		44,000,000
81	NVR4116HS-4KS2/L	4K	16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16–ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support		43,500,000
82	NVR4216-4KS2/L	4K UPGRADED	16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8–ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)		55,500,000
83	NVR4232-4KS2/L	NEW 4K AI	32 Channel 1U 2HDDs Network Video Recorder Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with attributes, perimeter protection, IVS, people counting, heat map, and SMD, Human & Vehivle Classification 2 SATA III ports, up to 10 TB each port, 1 × front USB2.0; 1 × back USB2.0 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)		66,900,000
84	NVR4232-4KS2	4K	32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*1000Mbps Network Card, P2P support		66,900,000
85	DHI-NVR5232-4KS2(V2.0)	4K	32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out , P2P Support		115,000,000
86	NVR4432-4KS2	4K	32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding, Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 4 SATA HDD up to 6TB, 2 USB Ports (1 USB2 & 1 USB3) 16 Alarm Input, 4 Relay Output, RS232 , RS485 2*10/100/1000Mbps Mbps Network Card, P2P support		96,100,000

ردیف	مدل		مشخصات فنی	تصویر	قیمت (ریال)
87	NVR5432-4KS2(V2.0)	4K	32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support		161,000,000
88	DHI-NVR5464-4KS2(V2.0)	4K	64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support		188,000,000
89	NVR4832-4KS2	4K	32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth, Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 8 SATA HDD up to 6TB, 3 USB Ports (2 USB2.0, 1 USB3.0) 16 Alarm Input, 4 Relay Output, RS232 , RS485 2*10/100/1000Mbps Mbps Network Card, P2P support		153,000,000
90	NVR5832-4KS2	4K	32 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&playback Max 16ch@1080P | 4ch@4K H.265 | H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10		224,000,000
91	DHI-NVR5864-4KS2(V2.0)	4K	64 Channel 2U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support		283,000,000
92	NVR608-32-4KS2	4K	Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output		241,000,000
93	NVR608-64-4KS2	4K	Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output		399,000,000
94	DHI-NVR608-128-4KS2	4K	128 Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA Port Support Raid 0/1/5/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output		480,000,000
95	ESS1508C		2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection		82,000,000
96	PFS3006-4ET-60		4-Port Fast Ethernet PoE Switch, Layer two commercial switch 2*10/100 Mbps Uplink ports, 4*10/100 Mbps PoE ports Port1≤60W, Port2-4≤30W, Total≤60W Support IEEE802.3af, IEEE802.3at(PoE+) ,Hi PoE 1.8Gbps Switching Capacity 890Kpps Mpps Packet Forwarding Rate 768Kb Packet Buffer Memory MAC Table size is 2K, Supports DC 48-57V power supply		11,700,000
97	PFS3010-8ET-96		8-Port Fast Ethernet PoE Switch, Layer two commercial switch 2*10/100/1000 Mbps Ports, 8*10/100 Mbps PoE Ports Port1≤60W, Port2-8≤30W, Total≤96W Support IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE 5.6Gbps Switching Capacity, 4.17 MppsPacket Forwarding Rate 4Mb Packet Buffer Memory MAC Table Size is 16K, Supports DC 48-57V power supply		21,400,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
98	PFS3110-8P-96	Two-layer industrial PoE switch 1*1000 Base-X, 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply) Each POE power ≤30W, Total≤96W Support IEEE802.3af, IEEE802.3at standard 7.6G Switching Capacity, 4.17 MppsPacket Forwarding Rate 1Mb Packet Buffer Memory, Industrial wide temperature design MAC auto study and aging, MAC address list capacity is 8K		26,700,000
99	PFS4218-16ET-190	Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤190W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity,5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)		67,500,000
100	PFS4218-16ET-240	Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)		73,000,000
101	PFS4226-24ET-240	24-Port PoE Switch, Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply), Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤240W, Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP, Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)		80,600,000
102	PFS4226-24ET-360	24-Port PoE Switch, Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤360W, Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Support Web management, Non-blocking video transmission management, PoE Setting/Event Statistics/Green PoE		96,700,000
103	PFS4226-24GT-360	24-Port PoE Gigabit Managed Switch Layer 2 network management PoE switch 24*10/100/1000 Base-T (PoE power supply) 2*100/1000 Base-X, Port1/2 support Hi-PoE (60W) Each power ≤30W, PoE Budget≤360W Spanning tree: STP/RSTP/MSTP Network management based on SNMP Configuration: Web, Telnet, CLI Command Support Vlan:VLAN/802.1Q Standard Vlan, 8K MAC Table 52G Switching Capacity, 38.688 Mpps Packet Forwarding Rate EMC high protection design		123,000,000
104	PFT1300	PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption <=8W), max transmission distance 300m		5,150,000
105	PFM700	*1 Channel HDMI Transmission Signal *1080P/1080I/720P/576P/576I/480P/480I Resolution Output Signal , *60M (max)Transmission Distance *Input voltage DC5V *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3		14,400,000
106	NKB1000	Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server, Connection : RS485, RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control, On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB		83,000,000