HIKVISION

لیست قیمت رسمی نیمه اردیبهشت ۱۴۰۲

www.npico.ir

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

نمایندگی مرکزی محصولات هایک ویژن

	1	2	3	4	5	6
Click for More information	DS-2CD1023G0E-I	DS-2CD1023G0-IUF	DS-2CD1043G0-I	DS-2CD1057G0-L	DS-2CD1123G0E-I	DS-2CD1323G0E-I
www.npico.ir						
Price (Rials)	۲۸,۹۰۰,۰۰۰	۴۰,۷۷۰,۰۰۰	۴۲,۳۱۰,۰۰۰	۵۸,۸۶۰,۰۰۰	۲۹,۹۱۰,۰۰۰	۲۹,۵۹۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Dome	Dome
Imaging Sensor	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS	1/2.7" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	2MP(1920x1080/30FPS)	4MP(2560×1440/20fps)	5MP (2560 × 1920/20fps)	2MP(1920x1080/30FPS)	2MP(1920x1080/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F1.2	0.01Lux @ F2.0
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	112.1°/90.2°	112.1°/90.2°	98°/78.7°	95°/76°	114.8°/86°	105°/81°
IR Range	Up to 30m	Up to 30m (EXIR)	Up to 30m	Up to 30m (Color Vu)	Up to 30m	Up to 30m (EXIR)
Body Type & Standard	Plastic / IP67	Metal/Plastic / IP67	Plastic / IP67	Metal / IP67	Plastic / IP67	Metal/Plastic / IP67
SD Card Support	No	Yes (Up to 256G)	No	Yes (Up to 256G)	No	No
Microphone Support	No	Yes (Built in MIC)	No	No	No	No
WDR	DWDR	DWDR	DWDR	Yes (120db)	DWDR	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP

	7	8	9	10	11	12
Click for More information	DS-2CD1353G0-I (2.8mm)	DS-2CD1357G0-L	DS-2CD1143G0-I	DS-2CD1143G0-IUF	DS-2CD1153G0-I	DS-2CD2021G1-I (2.8mm)
www.npico.ir						
Price (Rials)	۵۷,۰۰۰,۰۰۰	۵۸,۷۹۰,۰۰۰	۴۷,۴۶۰,۰۰۰	۵۵,۹۶۰,۰۰۰	۵۴,۵۴۰,۰۰۰	۴۹,۹۸۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Bullet
Imaging Sensor	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS
Resolution	5MP(2560x1920/20FPS)	5MP(2560x1920/20FPS)	4MP(2560×1440/20fps)	4MP(2560×1440/20fps)	5MP(2560x1920/15FPS)	2MP(1920x1080/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2.0	0.001Lux @ F1.0	0.028Lux @ F2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.005Lux @ F1.6
Lens	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	98.0°	95°/76°	98°/78.7°	98°/78.7°	98°/75.3°	111.6°/91.5°
IR Range	Up to 30m (EXIR)	Up to 30m (Color Vu)	Up to 30m	Up to 30m (Color Vu)	Up to 30m	Up to 30m (EXIR)
Body Type & Standard	Metal/Plastic / IP67	Metal/Plastic / IP67	Plastic / IP67	Plastic / IP67/ IK10	Plastic / IP67/ IK10	Metal/Plastic / IP67
SD Card Support	No	No	No	Yes (Up to 256 G)	No	Yes (Up to 256 G)
Microphone Support	No	No	No	Yes (Built in MIC)	No	No
WDR	Yes (120db)	Yes (120db)	DWDR	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, H.265+ COMP

	13	14	15	16	17	18
Click for More information	DS-2CD2H25FWD-IZS	DS-2CD2027G2-L (2.8mm)	DS-2CD2043G2-I (2.8mm)	DS-2CD2043G2-IU(2.8mm)	DS-2CD2047G2-L	DS-2CD2063G2-I
www.npico.ir						
Price (Rials)	۱۳۸,۸۷۰,۰۰۰	۷۱,۰۴۰,۰۰۰	۶۶,۴۶۰,۰۰۰	۷۹,۰۷۰,۰۰۰	۷۷,۷۰۰,۰۰۰	۷۲,۷۷۲,۰۰۰
Camera Type	Dome	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/2.8" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/1.8" Prog. CMOS	1/2.4" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	4MP(2560×1440/30fps)	4MP(2560×1440/30fps)	4MP(2560×1440/30fps)	6MP(2560×1440/30fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005Lux @ F1.2	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.0005Lux @ F1.0	0.005Lux @ F1.6
Lens	2.8-12mm Motorized	2.8 mm Fixed	2.8 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	105°~35°	107°	103°	103°	112°/95°	105°/78°
IR Range	Up to 30m	Up to 40m (Color Vu)	Up to 40m	Up to 40m	Up to 40m (Color Vu)	Up to 40m
Body Type & Standard	Metal / IP66/IK10	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 128 G)	Yes (Up to 256 G)	Yes (Up to 256 G)	Yes (Up to 256 G)	Yes (Up to 256 G)	Yes (Up to 512 G)
Microphone Support	Yes (1.ch Audio Input)	No	No	Yes (Built in MIC)	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (130db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, HLC, H.265+ COMP, DarkFighter	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC, H.265+ COMP

	19	20	21	22	23	24
Click for More information	DS-2CD2087G2-LU (2.8mm)	DS-2CD2126G2-ISU(2.8mm)	DS-2CD2347G2-L(2.8mm)	DS-2CD2347G2-LU(2.8mm)	DS-2CD2143G2-IU	DS-2CD2163G2-IU
www.npico.ir						
Price (Rials)	۱۵۶,۵۵۰,۰۰۰	۸۱,۵۴۰,۰۰۰	۷۸,۹۱۰,۰۰۰	۸۹,۷۶۰,۰۰۰	۶۱,۵۰۰,۰۰۰	۶۹,۰۰۰,۰۰۰
Camera Type	Bullet	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/1.2" Prog. CMOS	1/2.8" Prog. CMOS	1/1.8" Prog. CMOS	1/1.8" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	8MP(3072×1728/20fps)	2MP(1920x1080/25FPS)	4MP(2688 × 1520/25fps)	4MP(2688 × 1520/25fps)	4MP(2688 × 1520/25fps)	6MP(3200 × 1800/25fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.0005Lux @ F1.0	0.002 Lux @ F1.4	0.0005 Lux @ F1.0	0.0005 Lux @ F1.0	0.005 Lux @ F1.6	0.005 Lux @ F1.6
Lens	2.8 mm Fixed	2.8 mm Fixed	2.8 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	102°	107°	112°	112°	103°/84°	107°/87°
IR Range	Up to 40m (ColorVu)	Up to 30m	Up to 30m (Color Vu)	Up to 30m (Color Vu)	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP67	Metal / IP67 & IK10	Metal / IP67	Metal / IP67	Metal / IP67 & IK10	Metal / IP67 & IK10
SD Card Support	Yes (Up to 256 G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)
Microphone Support	Yes (Built in MIC)	Yes (Built in MIC)	No	Yes (Built in MIC)	Yes (Built in MIC)	Yes (Built in MIC)
WDR	Yes (130db)	Yes (120db)	Yes (130db)	Yes (130db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC, H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP, DarkFighter	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP

	25	26	27	28	29	30
Click for More information	DS-2CD2183G2-IU	DS-2CD2T43G2-2I(4mm)	DS-2CD2T43G2-4I(4mm)	DS-2CD2T63G2-4I	DS-2CD2T83G2-4I	DS-2CD2T86G2-4I
www.npico.ir						
Price (Rials)	۷۴,۲۵۰,۰۰۰	۷۶,۱۴۰,۰۰۰	۷۸,۷۲۴,۱۰۰	۸۰,۸۶۰,۰۰۰	۹۳,۹۰۰,۰۰۰	۱۲۱,۴۴۱,۰۰۰
Camera Type	Dome	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/2.5" Prog. CMOS	1/1.8" Prog. CMOS
Resolution	8MP(3840 × 2160/25fps)	4MP(2688×1520/25fps)	4MP(2688×1520/25fps)	6MP(3200×1800/25fps)	8MP(3840 × 2160/15fps)	8MP(3840 × 2160/25fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005 Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.2	0.003Lux @ F1.6
Lens	2.8/4 mm Fixed	4 mm Fixed	4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	107°/87°	84°	84°	107°/87°	102°/79°	111°/87°
IR Range	Up to 30m	Up to 60m (EXIR)	Up to 80m (EXIR)	Up to 80m (EXIR)	Up to 80m (EXIR)	Up to 80m (EXIR)
Body Type & Standard	Metal / IP67 & IK10	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)
Microphone Support	Yes (Built in MIC)	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, HLC,H.265+ COMP	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, HLC,H.265+ COMP, ROI	3D DNR, BLC, HLC,H.265+ COMP, ROI

	31	32	33	34	35
Click for More information	DS-2CD1643G0-IZ	DS-2CD1743G0-IZ	DS-2CD2643G2-IZS	DS-2CD2743G2-IZS	DS-2CD2786G2-IZS
www.npico.ir					
Price (Rials)	۸۱,۳۵۰,۰۰۰	۹۱,۳۴۰,۰۰۰	۱۲۴,۶۶۰,۰۰۰	۱۳۲,۷۶۰,۰۰۰	۱۹۵,۹۷۰,۰۰۰
Camera Type	Bullet	Dome	Bullet	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/1.8" Prog. CMOS
Resolution	4MP(2560 × 1440/20fps)	4MP (2560x1440/20fps)	4MP(2688 × 1520/25fps)	4MP (2560x1440/20FPS)	8MP(3840 × 2160/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.005Lux @ F1.6	0.003Lux @ F1.4
Lens	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized
Viewing Angle	102°~31°	91.2°~28.3°	95.8°~29.2°	104°~29°	108°~46°
IR Range	Up to 50m (EXIR)	Up to 30m (EXIR)	Up to 60m	Up to 40m	Up to 40m
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67,IK10	Metal / IP67,IK10	Metal / IP66,IK10
SD Card Support	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 128G)	Yes (Up to 256G)
Microphone Support	No	No	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP, Deep Learning	3D DNR, BLC, HLC, H.265+ COMP, Deep Learning, DarkFighter

	36	37
Click for More information	DS-2DE4225IW-DE S6	DS-2DE4425IW-DE T5
www.npico.ir		
Price (Rials)	۲۲۲,۵۱۰,۰۰۰	۲۵۲,۱۰۰,۰۰۰
Camera Type	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/60FPS)	4MP(2560 × 1440/30FPS)
Network Standard	ONVIF	ONVIF
Min. Illustration	0.005Lux/F1.6	0.005Lux/F1.6
Lens	4.8-120mm Motorized	4.8-120mm Motorized
Viewing Angle	25x	25x
IR Range	Up to 100m	Up to 100m
Body Type & Standard	Metal/IP66	Metal/IP66
SD Card Support	Yes (Up to 256G)	Yes (Up to 256G)
Microphone Support	No	No
WDR	Yes (120db)	Yes (120db)
WIFI	No	No
Power Supply	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)
Other Features	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

	38	39	40	41	42	43
Click for More information	DS-7104NI-Q1/M	DS-7108NI-Q1/M	DS-7604NI-K1	DS-7604NI-K1/4P	DS-7608NI-Q2	DS-7608NI-K1
www.npico.ir						
Price (Rials)	۴۲,۳۸۰,۰۰۰	۴۹,۳۸۰,۰۰۰	۶۱,۵۶۰,۰۰۰	۸۲,۷۴۰,۰۰۰	۸۰,۰۰۰,۰۰۰	۶۸,۳۴۰,۰۰۰
NVR Type	4 Ch	8 Ch	4 Ch	4 Ch / 4 POE	8 Ch	8 Ch
Input BandWidth	40Mbps	60Mbps	40Mbps	40Mbps	80Mbps	80Mbps
Output Bandwidth	60Mbps	60Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 4Mp	Upto 4Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	-	-	4 POE Ports	-	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 8TB	1 HDD up to 8TB
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M	1 RJ45 100M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Features	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP	H.265+ COMP Alarm I/O 4/1

	44	45	46	47	48	49
Click for More information	DS-7608NI-K1/8P	DS-7616NI-Q2	DS-7716NI-Q4	DS-7716NI-Q4/16P	DS-7616NI-K1	DS-7732NI-K4
www.npico.ir						
Price (Rials)	۱۲۶,۱۹۰,۰۰۰	۸۹,۸۱۰,۰۰۰	۱۷۸,۱۰۰,۰۰۰	۲۵۵,۱۴۰,۰۰۰	۸۵,۸۰۰,۰۰۰	۲۱۰,۳۱۰,۰۰۰
NVR Type	8 Ch / 8 POE	16 Ch	16 Ch	16 Ch / 16 POE	16 Ch	32 Ch
Input BandWidth	80Mbps	160Mbps	160Mbps	160Mbps	160Mbps	256Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	160Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	8 POE Ports	-	-	16 POE Ports	-	-
SATA Interface	1 HDD up to 8TB	2 HDD up to 8TB	4 HDD up to 8TB	4 HDD up to 8TB	1 HDD up to 8TB	4 HDD up to8TB
Network Interface	1 RJ45 100M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	2 RJ45 1000M
Chassis	Standalone 1U	1U	1.5U	1.5U	Standalone 1U	19" 1.5 Case
Other Features	H.265+ COMP Alarm I/O 4/1	H.265+ COMPR	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR	H.265+ COMPR Alarm I/O 16/4

	50	51	52
Click for More information	DS-7732NI-K4/16P	DS-9632NI-I8	IDS-9664NXI-I8/S
www.npico.ir			
Price (Rials)	۳۳۴,۳۱۰,۰۰۰	۷۱۰,۰۰۰,۰۰۰	۷۷۰,۰۰۰,۰۰۰
NVR Type	32 Ch / 16 POE	32 Ch	64 Ch
Input BandWidth	256Mbps	320Mbps	320Mbps
Output Bandwidth	160Mbps	256Mbps	256Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out
Decoding Capacity	Upto 8Mp	Upto 12Mp	Upto 12Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P
POE Ports	16 POE Ports	-	-
SATA Interface	4 HDD up to 8TB	8 HDD up to 10TB	8 HDD up to 10TB
Network Interface	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
Chassis	19" 1.5 Case	19" 1.5 Case	2U
Other Features	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4, RAID	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind