

1	DH-IPC-HFW5842EP-ZE	<p>8MP IR Vari-focal Bullet WizMind Network Camera            &gt; 8MP 1/1.8" CMOS image sensor, low illuminance, high image definition ( high definition image).            &gt; Outputs max. 8MP (3840x 2160) @30 fps.            &gt; Max. IR distance: 60 m. &gt; ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments &gt; Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes &gt; Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card.            &gt; 12V DC/PoE power supply. &gt; ePoE, IP67, IK10 protection.&gt; SMD 3.0</p>  	ج.م ٢٧٢,٩٨٧,...
2	DH-IPC-HFW5541EP-ZE	<p>5MP IR Vari-focal Bullet WizMind Network Camera            &gt; 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.            &gt; Outputs max. 5 MP (2592 x 1944)@20 fps.            &gt; Built-in IR LED, and the max. illumination distance is 60 m.            &gt; ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments.            &gt; Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. &gt; Three switchable intelligent resources: IVS, face detection, and people counting.            &gt; Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card.            &gt; 12 VDC/PoE power supply, easy for installation.            &gt; IP67 and IK10 protection; ePoE. &gt; SMD 3.0.</p>  	ج.م ١,٩٢٠,...
3	DH-IPC-HFW5541TP-ASE	<ul style="list-style-type: none"> <li>• 1/2.7" 5Megapixel progressive scan CMOS</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• 20 fps@2592 x 1944, 50/60 fps@1080P (1920 x 1080)</li> <li>• WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS (DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6 mm, 6.0 mm, 8.0 mm, 12.0 mm optional)</li> <li>• 1/1 Alarm in/out, 1/1 audio in/out</li> <li>• Max. IR LEDs Length 80 m</li> <li>• Micro SD memory, IP67,IK10</li> </ul>  	ج.م ١٣٣,٧١٦,...
4	DH-IPC-HFW5442EP-ZE	<ul style="list-style-type: none"> <li>• 1/1.8" 4Megapixel progressive scan CMOS (AI-SATRILIGHT)</li> <li>• H.265 &amp; H.264 triple-stream encoding</li> <li>• 25/30 fps@2688 x 1520, 50/60 fps@1080P(1920 x 1080)</li> <li>• WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS (DSS/PSS) &amp; DMSS</li> <li>• 2.7 mm-12.0 mm motorized lens</li> <li>• 2/1 Alarm in/out, 1/1 audio in/out</li> <li>• Max. IR LEDs Length 50 m</li> <li>• Micro SD memory, IP67, IK10</li> </ul>  	ج.م ٢٣١,٠٥٥,...
5	DH-IPC-HFW3449EP-AS-LED	<ul style="list-style-type: none"> <li>• 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 x 1520) @ 30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in Warm LED, max. LED distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic</li> <li>• 12V DC/PoE power support</li> <li>• IP67 protection · SMD Plus</li> </ul>  	ج.م ٨٦,٦٧٠,...

- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 G Micro SD card, built-in Mic
- 12V DC/POE power supply
- IP67 protection • SMD Plus

6 DH-IPC-HFW3441EP-SA



٢٢,١٨٠,٠٠ ج.م

7 DH-IPC-HFW3441EP-AS



٧٥,٤٠٠,٠٠ ج.م

8 DH-IPC-HFW2831TP-ZS



١٥١,١٢٥,٠٠ ج.م

9 DH-IPC-HFW2831SP-S

- 8MP Lite IR Fixed-focal Bullet Network Camera
- > 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- > Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps
- > H.265 codec, high compression rate, ultra-low bit rate
- > Built-in IR LED, max IR distance: 30 m
- > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire • Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection > Supports max. 256 GB Micro SD card> 12V DC/PoE power supply> IP67 protection



١١١,٨٣٠,٠٠ ج.م

10	DH-IPC-HFW2531TP-ZS	<ul style="list-style-type: none"> <li>• 1/2.7" 5Megapixel progressive CMOS <b>STARLIGHT</b></li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 15fps@5M(2592×1944)&amp;25/30fps@3M(2304×1296)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• Micro SD card slot, up to 128GB • IP67, PoE+</li> <li>• 2.7~13.5mm motorized lens· Max IR LEDs Length 60m</li> </ul>			١٢٢,٩٠,...
11	DH-IPC-HFW2531SP-S	<p>.5MP Lite IR Fixed-focal Bullet Network Camera <b>STARLIGHT</b></p> <ul style="list-style-type: none"> <li>• 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire</li> <li>• Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>IP67 protection</li> </ul>			٧٠,٥١,...
12	DH-IPC-HFW2431TP-ZS	<ul style="list-style-type: none"> <li>• 1/3" 4Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 20fps@4M(2688×1520)&amp;25/30fps@3M(2304×1296)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• Micro SD card slot, up to 128GB</li> <li>• 2.7~13.5mm motorized lens· Max IR LEDs Length 60m</li> <li>• IP67, IK10(optional), PoE+</li> </ul>			٩٩,٩٤٦,٥٠...
13	DH-IPC-HFW2431SP-S	<ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, <b>Starlight</b></li> <li>• Outputs 4MP (2560 × 1440) @25/30fps, Max. supports 4MP (2688 × 1520) @20 fps</li> <li>• H.265 codec, high compression ration, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire · IP67 protection</li> <li>• Abnormality detection: Motion detection, video tampering, no SD</li> <li>• Supports max. 256 GB Micro SD card · 12V DC/PoE power support</li> </ul>			٥٥,١٢,...
14	DH-IPC-HFW2231TP-ZS	<ul style="list-style-type: none"> <li>• 1/2.8" 2Megapixel progressive <b>STARVIS™</b> CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920×1080)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• Micro SD card slot, up to 128GB</li> <li>• 2.7~13.5mm motorized lens· Max IR LEDs Length 60m</li> <li>• IP67, IK10(optional), PoE</li> </ul>			٨٨,٢١,...

15	DH-IPC-HFW1831EP	<ul style="list-style-type: none"> <li>• 1/1.8" 8Megapixel progressive scan CMOS</li> <li>• H. 265&amp;H.264 dual-stream encoding</li> <li>• 25/30fps@8MP(3840×2160)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8mm fixed lens (4mm, 6mm optional)</li> <li>• Max. IR LEDs Length 50m IP67, PoE</li> </ul>		١١٥,٤٣٠,٠٠
16	DH-IPC-HFW1431SP		<ul style="list-style-type: none"> <li>• 1/3" 4Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6 mm optional)</li> <li>• Max IR LEDs Length 30m IP67, PoE</li> </ul>	٤٧,٥٠٥,٢٠
17	DH-IPC-HFW1431S1P		<ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• 12V DC/PoE power support</li> <li>• IP67, protection</li> </ul>	٤٢,٦٧٤,٩٠
18	DH-IPC-HFW1230T1P-ZS		<ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080p) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 50 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	٦١,٨٣٦,٠٠
19	DH-IPC-HFW1230SP		<ul style="list-style-type: none"> <li>• 1/2.7" 2Megapixel progressive CMOS</li> <li>• H.265&amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920×1080)</li> <li>• DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6mm optional)</li> <li>• Max IR LEDs Length 30m IP67, PoE</li> </ul>	٣٦,٩١٠,٠٠

		<b>Human Detection</b> 1080P 360° Coverage Built-in Siren Smart Tracking Privacy Mode Abnormal Sound Alarm Night Vision Two-way Talk Cloud			٢٥,١٢٠,٠٠٠
20	IPC-A22EP				
21	DH-IPC-K100W	<ul style="list-style-type: none"> <li>• 1/3" 1.3Megapixel Aptina CMOS</li> <li>• H.264 &amp; MJPEG dual-stream encoding</li> <li>• Max 15fps@1.3M (1280×960)/25/30fps@720P(1280×720)</li> <li>• DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 3.6mm fixed lens • White LEDs length 10m</li> <li>• PIR sensor range 6m • Micro SD memory . Wi-Fi</li> </ul>		٢٩,٣٠٠,٠٠٠	
22	DH-IPC-K22P	<ul style="list-style-type: none"> <li>. 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>. Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>. H.265 codec, high compression rate, ultra-low bit rate</li> <li>. Max. IR distance: 10 m</li> <li>. Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>. H.264/H.265, flexible coding, applicable to various bandwidth and storage environments.</li> <li>. Alarm: 1 in, 1 out; 256 G SD card, built-in Mic and speaker</li> <li>. Supports 256 G Micro SD card</li> <li>. 12V DC power supply, easy for installation</li> <li>. Supports PIR .Supports Wi-Fi</li> </ul>			٣٧,٨٣٠,٠٠٠
23	DH-IPC-HDBW5842EP-ZE	 <ul style="list-style-type: none"> <li>. 8MP IR Vari-focal Dome WizMind Network Camera</li> <li>. 8 MP 1/1.8" CMOS image sensor, low luminance, and high definition image</li> <li>. Outputs max. 8MP (3840×2160) @30 fps, Max. IR distance: 80 m</li> <li>. ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>. Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card</li> <li>. 24V AC/PoE/12V DC power supply</li> <li>. ePoE, IP67, IK10 protection, SMD 3.0</li> </ul>			٤٨٤,٨٥٦,٠٠٠
24	DH-IPC-HDBW5831RP-ZE	 <ul style="list-style-type: none"> <li>. 8MP WDR IR Dome Network Camera</li> <li>&gt; 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS</li> <li>&gt; H.265&amp;H.264 dual-stream encoding</li> <li>&gt; 15fps@4K(3840×2160),25/30fps@3M(2304×1296)</li> <li>&gt; Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>&gt; Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>&gt; 2.7mm ~12mm motorized lens</li> <li>&gt; Max. IR LEDs Length 50m</li> <li>&gt; Micro SD card memory, IP67,IK10, PoE</li> </ul>			١٨٥,٩٦٠,٠٠٠

25	DH-IPC-HDBW5541EP-ZE	ePoE		٢١٢,٢٠٠,...
26	DH-IPC-HDBW5442EP-ZE	ePoE		٢٣٤,٩٧٢,...
27	DH-IPC-HDW5541TMP-ASE	ePoE		١٢٦,٨٢٠,...
28	DH-IPC-HDW5431RP-ZE	ePoE		#N/A
29	DH-IPC-HDBW3441RP-ZS			١٢١,٨٦٠,...

30 DH-IPC-HDW3449TMP-AS-LED

- 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520) @ 30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in Warm LED, max. LEDs distance: 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 G Micro SD card, built-in Mic
- 12V DC/PoE power support
- IP67 protection · SMD Plus



ج.م. ٢٧٠,٨٠٠



31 DH-IPC-HDBW3441EP-AS

- 4MP IR Fixed focal Dome WizSense Network Camera, STARLIGHT
- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card
- 12V DC/POE power supply
- IP67, IK10 protection, SMD Plus



ج.م. ١٨٠,٨٠٠



32 DH-IPC-HDBW3441EP-S

- 4MP IR Fixed focal Dome WizSense Network Camera
- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing,no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 G Micro SD card
- 12V DC/POE power supply
- IP67, IK10 protection, SMD Plus



ج.م. ٢٤,٧٨٠,٠٠



33 DH-IPC-HDBW2831RP-ZS

- 1/1.8" 8Megapixel progressive CMOS
- H.265 & H.264 dual-stream encoding
- 25/30fps@8MP(3840×2160)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Micro SD card slot, up to 128GB · IP67, IK10, PoE
- 3.7~11mm motorized lens- Max IR LEDs Length 30m



ج.م. ٦٢,٥٠٠



34

DH-IPC-HDBW2531RP-ZS

- . 5MP WDR IR Dome Network Camera P6730m
- 1/2.7" 5Megapixel progressive CMOS
- H.265 & H.264 dual-stream encoding
- 15fps@5M(2592×1944)&25/30fps@3M(2304×1296)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Micro SD card slot, up to 128GB
- 2.7~13.5mm motorized lens
- Max IR LEDs Length 30m, IP67, IK10, PoE



١١٥,٤٣٠,٠٠ ج.م

35

DH-IPC-HDBW2431RP-ZS

- . 1/3" 4MP WDR IR Dome Network Camera
- H.265 & H.264 dual-stream encoding
- 20fps@4M(2688×1520)&25/30fps@3M(2304×1296)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Micro SD card slot, up to 128GB
- 2.7~13.5mm motorized lens
- Max IR LEDs Length 30m · IP67, IK10, PoE



٨٠٨,٤٠٠,٠٠ ج.م

36

DH-IPC-HDBW2531EP-S

- . 5MP Lite IR Fixed-focal Dome Network Camera, STARLIGHT
- 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max IR distance: 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire
- Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
- Supports max. 256 GB Micro SD card
- 12V DC/PoE power supply
- IP67, IK10 protection



٧٠٥,٥١٠,٠٠ ج.م

37

DH-IPC-HDW2439TP-AS-LED

- 4MP Lite Full-color Fixed-focal Eyeball Network Camera
- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in warm lights, max. illumination distance: 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire
- Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 GB Micro SD card and built-in Mic
- 12V DC/PoE power supply, IP67 protection



٦٧,٣٠٠,٠٠ ج.م

38	DH-IPC-HDBW2431EP-S	<ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, <b>Starlight</b></li> <li>• Outputs 4MP (2560 × 1440) @25/30 fps, max. supports 4MP</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire</li> <li>• Abnormality detection: Motion detection, video tampering, no SD</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power support • IP67, IK10 protection grade</li> </ul>	      		ریال ۱۲۰,۰۰۰
39	DH-IPC-HDBW1431EP	<ul style="list-style-type: none"> <li>• 1/3" 4Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6 mm optional)</li> <li>• Max IR LEDs Length 30m• IP67, IK10, PoE</li> </ul>	     		ریال ۱۴۰,۰۰۰
40	DH-IPC-HDBW2231RP-ZS	<ul style="list-style-type: none"> <li>• 2MP WDR IR Dome Network Camera</li> <li>• 1/2.8" 2Megapixel progressive StarvisTM CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920×1080)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• Micro SD card slot, up to 128GB</li> <li>• 2.7~13.5mm varifocal lens</li> <li>• Max IR LEDs Length 30m</li> <li>• IP67, IK10, PoE</li> </ul>	     		ریال ۱۹۰,۰۰۰
41	DH-IPC-HDW1431T1P	<ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• 12V DC/PoE power support</li> <li>• IP67, protection</li> </ul>	    		ریال ۱۴۰,۰۰۰
42	DH-IPC-HDW2231TP-AS	<ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264+H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire</li> <li>• Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card, built-in Mic</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	     		ریال ۱۷۰,۰۰۰

43

DH-IPC-HDBW1230EP



- . 1/2.7" 2Megapixel progressive CMOS
- . H.265 & H.264 dual-stream encoding
- . 25/30fps@1080P(1920x1080)
- . DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- . Multi-in network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- . 2.8mm fixed lens (3.6mm optional)
- . Max IR LEDs length 30m . IP67, IK10, PoE



٣٨,٤٦٠,٠٠ ريال

44

DH-IPC-HDW1230T1P



- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080p) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max. IR distance: 30 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection



٣٥,٣٥٦,٨٠٠ ريال

45

DH-IPC-HDW1239T1P-LED



- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in LEDs, max LED distance: 15 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection



٣٨,٤٦٠,٠٠ ريال

46

DH-IPC-HFW2439SP-SA-LED



- 4MP Lite Full-color Fixed-focal Bullet Network Camera
- . 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- . Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps
- . H.265 codec, high compression rate, ultra-low bit rate
- . Built-in warm lights, max. illumination distance: 30 m
- . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- . Intelligent detection: Intrusion, tripwire
- . Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- . Supports max. 256 GB Micro SD card and built-in Mic
- > IP67 protection



٦٧,٤٨٠,٠٠ ريال

47

DH-IPC-HFW1239S1P-LED

- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in LEDs, max LED distance: 15 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection



٣٧,٩٦,٠٠ ریال

48

DH-IPC-HFW1230S1P

- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max. IR distance: 30 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection



٣٤,٦٠,٠٠ ریال

49

DH-SD5A245GB-HNR

- > 1/2.8" 2Megapixel STARVIS™ CMOS.
- > 45x optical zoom.
- > Starlight technology.
- > Max. 25/30fps@1080P.
- > IR distance up to 150 m.
- > Auto-tracking 3.0.
- > Perimeter protection.
- > Face detection.
- > SMD 4.0.
- > Quick Pick.
- > IP67, IK10.



٤٣٣,١٠,٠٠ ریال

50

DH-SD5A432XB-HNR

- 1/2.8" 4Megapixel STARVIS™ CMOS
- Powerful 32x optical zoom
- Max. 25/30fps@4M
- IR distance up to 150 m
- Deep-learning-based auto tracking and perimeter protection
- SMD PLUS
- PoE+
- IP67, IK10
- Face Detection



٤٣,٢٢٥,٠٠ ریال

51

DH-SD5A432GB-HNR

- > 1/2.8" 4Megapixel STARVIS™ CMOS.
- > Powerful 32x optical zoom.
- > Max. 25/30 fps@4M.
- > IR distance up to 150 m.
- > Auto Tracking 3.0.
- > Face Detection.
- > SMD 4.0.
- > Quick Pick.
- > PoE+.
- > IP67, IK10.



٥٩٢,٤٩٠,٠٠ ریال

52	DH-SD5A232XB-HNR	<p>2MP 32x <b>Starlight</b> IR WizSense Network PTZ Camera          &gt; 1/2.8" 2Megapixel STARVIS™ CMOS          &gt; Powerful 32x optical zoom          &gt; Max. 50/60 fps@1080P          &gt; IR distance up to 150 m          &gt; Deep-learning-based auto tracking and perimeter protection          &gt; SMD PLUS          &gt; PoE+          &gt; IP67, IK10          &gt; Face Detection</p>  <p><b>ریال ٤٨٩,٦٧٠,٠٠</b></p>
53	DH-SD59230U-HNI	<p>2MP 25x <b>Starlight</b> IR WizSense Network PTZ Camera          &gt; 1/2.8" 2Megapixel STARVIS™ CMOS          &gt; Powerful 25x optical zoom          &gt; Max. 50/60 fps@1080P          &gt; IR distance up to 150 m          &gt; Deep-learning-based auto tracking and perimeter protection          &gt; SMD PLUS          &gt; PoE+          &gt; IP67, IK10          &gt; Face Detection</p>  <p><b>ریال ٥١٠,٤٠٠,٠٠</b></p>
54	DH-SD49225XA-HNR	<p>. 2MP 25x Starlight IR WizSense Network PTZ Camera          . 1/2.8" 2Megapixel CMOS          . Powerful 25x optical zoom          . Starlight technology          . Max. 50/60fps@1080P          . Perimeter protection . Support PoE+          . IR distance up to 100m . SMD PLUS . IP66</p>  <p><b>ریال ٢٩١,٣١٩,٦٠٠</b></p>
55	DH-SD29204UE-GN	<p>• 1/2.8" STARVIS™ CMOS . <b>STARLIGHT</b>          • Powerful 4x optical zoom          • Support Triple-streams encoding          • WDR, Day/Night(ICR), Ultra DNR          • Max. 25/30fps@1080P . IVS          • Support PoE . IR distance up to 30m</p>  <p><b>ریال ١٤٤,٩٢٠,٠٠</b></p>
56	DH-NVR1B04  EZ-IP	<p>. 4 Channel Smart 1U H.265 Network Video Recorder decoding          • Max 4 channel IP camera inputs          • Max 80Mbps incoming bandwidth          • Up to 8MP resolution preview&amp;playback          • Up to 1ch@8MP/4ch@1080P decoding          • HDMI/VGA simultaneous video output</p>  <p><b>ریال ٢٨,٢٤٠,٠٠</b></p>
57	DH-NVR1B04-4P  EZ-IP	<p>• H.265+/H.264+ codec decoding          • Max 4 channel IP camera inputs          • Max 80Mbps incoming bandwidth          • Up to 8MP resolution preview&amp;playback          • Up to 1ch@8MP/4ch@1080P decoding          • HDMI/VGA simultaneous video output          • Support IPC UPnP, 4PoE ports          . 1 SATA III Port, up to 6TB capacity for each HDD</p>  <p><b>ریال ٤٥,٧٢٠,٠٠</b></p>

58

DH-NVR104-P  


- . 4CH Smart Box 4PoE Network Video Recorder
- . Up to 4 channel IP camera input
- . H.264/MJPEG dual codec decoding
- . Max 56Mbps incoming bandwidth
- . HDMI/VGA simultaneous video output
- . All channel synchronous realtime playback, GRID interface
- . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0
- . Support IPC UPnP, 4PoE ports
- . Support P2P (QR code Scan)



٤١,٣٠,٠٠٠ ريال

59

DH-NVR108-P  


- . 8CH Smart Box 4PoE Network Video Recorder
- . Up to 8 channel IP camera input
- . H.264/MJPEG dual codec decoding
- . Max 56Mbps incoming bandwidth
- . HDMI/VGA simultaneous video output
- . All channel synchronous realtime playback, GRID interface
- . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0
- . Support IPC UPnP, 4PoE ports
- . Support P2P (QR code Scan)



٤٧,٨٢,٠٠٠ ريال

60

DH-NVR608-64-4KS2

- . Intel Quad-core Processor
- . 64 channel IPC input-32 Channel Live Preview:
- (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16)
- . H.265/H.264/MJPEG codec decoding
- . Max 384Mbps incoming bandwidth . 2HDMI/VGA simultaneous video output
- . Up to 12Mp resolution preview & playback . RS232 , RS485-16 Alarm In
- . Support 8 SATA HDDs up to 64TB,1 eSATA Port . Support Raid 0/1/5/6/10
- . Support Smart Tracking and Intelligent Video
- . 4 USB(2 USB3.0, 2 USB2.0)-2\*1000 Mbps Network Card



٩٨,٠٨,٠٠٠ ريال

61

DH-NVR608H-32-XI

- 32 Channels 2U 8HDDs WizMind Network Video Recorder
- > 32-channel 1080p self-adaptive decoding capability.
- > Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth.
- > Supports N+M cluster.
- > Support Raid0/1/5/6/10.
- > Drawer-like chassis design allows for HDD hot swapping.
- > AI by recorder: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus.
- > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting.



١٦١,٨٠٠,٠٠٠ ريال

62

DH-NVR608-32-4KS2

- . Intel Dual-core Processor-32 channel IPC input
- . 32 Channel Live Preview: 16 Alarm In , 8 Relay Output
- . (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16)
- . H.265/H.264/MJPEG codec decoding
- . Max 384Mbps incoming bandwidth
- . Up to 12Mp resolution preview&playback
- . 2HDMI/VGA simultaneous video output
- . Support 8 SATA HDDs up to 64TB,1 eSATA Port
- . Support Raid 0/1/5/6/10-4 USB(2 USB3.0, 2 USB2.0)
- . 2\*1000 Mbps Network Card-RS232 , RS485



٥٢,٩٥,٠٠٠ ريال

63

DH-NVR5864-EI

- 64 Channels 2U 8HDD WizSense Network Video Recorder**
- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
  - > 32-channel 1080p self-adaptive decoding capability.
  - > Support Raid0/1/5/6/10.
  - > Max. 384 Mbps incoming/recording/outgoing bandwidth.
  - > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
  - > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
  - > Security baseline 2.3.



ج.م ٦٣٩,٧٠٠,٠٠

64

DH-NVR5832-EI

- 32 Channels 2U 8HDD WizSense Network Video Recorder**
- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
  - > 32-channel 1080p self-adaptive decoding capability.
  - > Max. 384 Mbps incoming/recording/outgoing bandwidth.
  - > Support Raid0/1/5/6/10.
  - > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
  - > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
  - > Security baseline 2.3.



ج.م ٥٥٦,٧٠٠,٠٠

65

DH-NVR5832-4KS2

- . 32 channel IPC input-32 Channel Live Preview
- . H.265/H.264/MJPEG/MPEG4 codec decoding
- . Max 320Mbps incoming bandwidth . P2P Support-Raid 0/1/5/6/10
- . Up to 12Mp resolution preview&playback
- . Max 16ch@1080P | 4ch@4K H.265 | H.264 Playback
- . 2HDMI/VGA simultaneous video output
- . Support 8 SATA HDDs up to 64TB, 4 USB(2 USB3.0, 2 USB2.0)
- . 2\*1000 Mbps Network Card-RS232-16 Alarm In , 6 Relay Output



ج.م ٤٤٧,٨٧٦,٠٠

66

DH-NVR5432-16P-4KS2E

- . 32Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder
- . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- . Max 320Mbps Incoming Bandwidth
- . Up to 12MP Resolution for Preview and Playback
- . 2HDMI/VGA simultaneous video output
- . 3D intelligent positioning with Dahua PTZ camera
- . 4 SATA III Ports, Up to 8 TB capacity for each HDD



ج.م ٤٦١,٢٣٠,٠٠

67

DH-NVR5432-E1

- 32 Channels 1.5U 4HDD WizSense Network Video Recorder  
 > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.  
 > 32-channel 1080p self-adaptive decoding capability.  
 > Max. 384 Mbps incoming/recording/outgoing bandwidth.  
 > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.  
 > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.  
 > Security baseline 2.3.



ج.م. ٣٩٣,١٩٠,٠٠



68

DH-NVR5432-4KS2

- . 32 Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder  
 • Smart H.265+/H.265/Smart H.264+/H.264/MJPEG  
 • Max 320Mbps Incoming Bandwidth  
 • Up to 12MP Resolution for Preview and Playback  
 • 2HDMI/2VGA simultaneous video output  
 • 1-8 PoE Ports Support 800m ePoE & EoC



ج.م. ٣١٣,٣٧٥,٠٠



69

DH-NVR5232-E1

- 32 Channels 1U 2HDD WizSense Network Video Recorder  
 > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.  
 > 32-channel 1080p self-adaptive decoding capability.  
 > Max. 384 Mbps incoming/recording/outgoing bandwidth.  
 > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.  
 > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.  
 > Security baseline 2.3.



ج.م. ٢٧٥,٥٩٠,٠٠



70

DH-NVR5232-4KS2

- . 32 channel IP camera input.32 channel Live Preview  
 . Up to 12Mp resolution preview&playback  
 . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG  
 . Max 320Mbps incoming bandwidth-Record Rate 320 Mbps  
 . Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding  
 . HDMI/VGA simultaneous video output-16 channel playback  
 . Support 2 SATA HDDS up to 20TB, 2 USB(1 USB3.0)  
 . 1000 Mbps Network Card -RS232, RS485  
 . 4 Alarm Input, 2 Relay Output-Support P2



ج.م. ٢٤٤,٦٢٢,٤٠٠



71

DH-NVR5216-16P-I

**Wiz Mind**

- . 16Channel 1U 16PoE AI Network Video Recorder  
 • 16 Channel IP video access  
 • Smart H.265+/H.265/Smart H.264+/H.264/MJPEG  
 • Up to 16 Channel perimeter protection  
 • Up to 4 Channel video stream face recognition  
 • Up to 22 face pictures /sec processing  
 • Up to 20 face databases with 100,000 face images in total  
 • 1-8 PoE Ports support ePoE & EoC



ج.م. ٧٠,٠٤٠,٠٠



72

DH-NVR5216-16P-4KS2E

- .32 Channel 1U 2HDDs 16PoE 4K & H.265 Pro Network Video Recorder
- . 32-channel IP video access
- . Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch
- . Max 320 Mbps incoming bandwidth
- . Up to 24MP resolution for live view and playback
- . 1-channel fisheye dewarping (AI by NVR)
- . AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map
- . Support IPC UPnP, 16 PoE ports



ج.م ٢٨٧,٧٤١,٥٠٠

- 16 Channels 1U 2HDD WizSense Network Video Recorder
- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
  - > 32-channel 1080p self-adaptive decoding capability.
  - > Max. 384 Mbps incoming/recording/outgoing bandwidth.
  - > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
  - > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
  - > Security baseline 2.3



73

DH-NVR5216-EI

- . 16Channel 1U 4K&H.265 Pro Network Video Recorder (V2.00)
- . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- . Max 320Mbps Incoming Bandwidth
- . Up to 12MP Resolution for Preview and Playback
- . HDMI/VGA simultaneous video output
- . 2 SATA III Ports, Up to 10 TB capacity for each HDD



ج.م ٢٤٥,٠٧٠,٠٠٠



74

DH-NVR5216-4KS2

- . 32 channel IP camera input. 1.5U
- . 16 channel Live Preview-H.265/H.264 codec decoding
- . Max 200Mbps incoming bandwidth
- . Up to 8MP Resolution for Preview and Playback
- . HDMI/VGA simultaneous video output
- . Support 4 SATA HDD up to 6TB
- . 2 USB Ports (1 USB2.0, 1 USB3.0)
- . 16 Alarm Input, 4 Relay Output-RS232 , RS485
- . 2\*10/100/1000Mbps Mbps Network Card-P2P support



ج.م ٢٠٧,٤٦٠,٠٠٠



75

DH-NVR4432-4KS2

- . New 4.0 user interface, Security baseline 2.1
- . H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- . Max. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding
- . Supports mainstream cameras of ONVIF and RTSP protocols
- . P2P remote surveillance, video play on mobile device
- . VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- . AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- . Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



ج.م ١٩٩,٨١٠,٠٠٠



76

DH-NVR4232-4KS2/L

- . 32 Channel 1U 2HDDs 16PoE 4K & H.265 Pro Network Video Recorder
- . 32-channel IP video access
- . Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch
- . Max 320 Mbps incoming bandwidth
- . Up to 24MP resolution for live view and playback
- . 1-channel fisheye dewarping (AI by NVR)
- . AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map
- . Support IPC UPnP, 16 PoE ports



ج.م ١٤٠,٨٠٦,٠٠٠



77

DH-NVR4232-4KS2

- 32-channel IP video access
- Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch
- Max 200 Mbps incoming bandwidth
- Up to 8MP resolution for preview and playback
- 8-channel decoding@1080p (30 fps)
- AI by Camera: Perimeter protection; SMD Plus; people counting; heat map



۱۴۳,۳۹۰,۰۰۰ ریال

16 Channel 1U 2HDDs 16PoE Network Video Recorder- New 4.0 user interface, Security baseline

2.1

- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



78

DH-NVR4216-16P-4KS2/L

16 Channel 1U 2HDDs Network Video Recorder- New 4.0 user interface, Security baseline

2.1

- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



۱۹۳,۱۷۷,۰۰۰ ریال



79

DH-NVR4216-4KS2/L

.16 Channel 1U 2HDDs Network Video Recorder

- New 4.0 user interface, Security baseline 2.1
- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



۱۱۳,۰۲۲,۰۰۰ ریال



80

DH-NVR4116HS-4KS2/L

• New 4.0 user interface, Security baseline 2.1

- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



۱۶۹,۰۹۰,۰۰۰ ریال



- New 4.0 user interface, Security baseline 2.1
- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches

81 DH-NVR4108HS-8P-4KS2/L



١٥١,٧٦٧,٠٠

82 DH-NVR4108HS-4KS2



٦٥,٥٢٠,٠٠

83 DH-NVR4108HS-4KS2/L



- New 4.0 user interface, Security baseline 2.1
- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



٩٦٩,٩٦٠,٠٠

84 DH-NVR4104HS-P-4KS2/L



- New 4.0 user interface, Security baseline 2.1
- H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- Supports mainstream cameras of ONVIF and RTSP protocols
- P2P remote surveillance, video play on mobile device
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



٨٩,٨٦٨,٨٠

		<ul style="list-style-type: none"> <li>. 4 Channel Compact 1U 1HDD Network Video Recorder</li> <li>.. New 4.0 user interface, Security baseline 2.1</li> <li>· H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch</li> <li>· Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding</li> <li>· Supports mainstream cameras of ONVIF and RTSP protocols</li> <li>· P2P remote surveillance, video play on mobile device</li> <li>· VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K</li> <li>· AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD</li> <li>· Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</li> </ul>		
85	DH-NVR4104HS-4KS2/L		٦٤١,٤٠,٠٠٠	
86	DH-NVR2108HS-8P-4KS2	<ul style="list-style-type: none"> <li>. 8 Channel Compact 1U 8PoE Lite 4K</li> <li>· H.265/H.264 codec decoding . HDMI/VGA simultaneous video output</li> <li>· Max 80Mbps incoming bandwidth</li> <li>· Up to 8Mp resolution preview&amp;playback</li> <li>· Up to 1ch@8MP/4ch@1080P decoding</li> <li>· Support 1 SATA HDD up to 6TB, 2 USB2.0</li> <li>· 100 Mbps Network Card-8Port PoE. P2P support</li> </ul>		
			١٠٩,٠٠٠,٠٠٠	
87	DH-NVR2104HS-P-4KS2	<ul style="list-style-type: none"> <li>. 4 Channel Compact 1U 4PoE Lite 4K. H.265/H.264 codec decoding</li> <li>· Max 80Mbps incoming bandwidth-Up to 8Mp resolution</li> <li>· preview&amp;playback-Up to 1ch@8MP/4ch@1080P decoding</li> <li>· HDMI/VGA simultaneous video output</li> <li>· Support 1 SATA HDD up to 6TB, 2 USB2.0</li> <li>· 100 Mbps Network Card-4PoE Port. P2P support</li> </ul>		
			٧٦,٩٤٠,٠٠٠	
88	DH-NVR2108HS-4KS2	<ul style="list-style-type: none"> <li>. 8 channel IP camera input 1U Lite 4K</li> <li>· H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support</li> <li>· Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output</li> <li>· Up to 8Mp resolution preview&amp;playback</li> <li>· Up to 1ch@8MP/4ch@1080P decoding</li> <li>· Support 1 SATA HDD up to 6TB, 2 USB2.0</li> </ul>		
			٥٦,٤٢٠,٠٠٠	
89	DH-NVR2104HS-4KS2	<ul style="list-style-type: none"> <li>. 4 channel IP camera input 1U Lite 4K</li> <li>· H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support</li> <li>· Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output</li> <li>· Up to 8Mp resolution preview&amp;playback</li> <li>· Up to 1ch@8MP/4ch@1080P decoding</li> <li>· Support 1 SATA HDD up to 6TB, 2 USB2.0</li> </ul>		
			٤٨,٧٣٠,٠٠٠	

		<ul style="list-style-type: none"> <li>• New 4.0 user interface</li> <li>• P2P remote surveillance, video play on mobile device</li> <li>• 8-ch@1080P(30FPS), self-adaptive decoding capability</li> <li>• Support for mainstream cameras of ONVIF and RTSP protocol</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264</li> <li>• VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P</li> <li>• Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches</li> <li>• DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System)</li> </ul>	
90	DH-NVR1108HS-8P-S3/H		ریال ۷۴,۶۳۰,۰۰۰
91	DH-NVR1104HS-P-S3/H	<ul style="list-style-type: none"> <li>• New 4.0 user interface</li> <li>• P2P remote surveillance, video play on mobile device</li> <li>• 4-ch@1080P(30FPS), self-adaptive decoding capability</li> <li>• Support for mainstream cameras of ONVIF and RTSP protocol</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264</li> <li>• VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P</li> <li>• Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches</li> <li>• DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System)</li> </ul>	ریال ۵۲,۵۴۰,۰۰۰
92	DH-PFS3226-24ET-240	<ul style="list-style-type: none"> <li>&gt; Intelligent PoE</li> <li>&gt; PD Alive(PoE Watchdog)</li> <li>&gt; Long Distance PoE Transmission</li> <li>&gt; Smooth Transmission</li> <li>&gt; Wide Working Temperature: -10 to 55°C (14°F to 131°F)</li> <li>&gt; Port Isolation</li> </ul>	ریال ۱۹۷,۳۶۰,۰۰۰
93	DH-PFS3218-16ET-135	<ul style="list-style-type: none"> <li>&gt; Intelligent PoE</li> <li>&gt; PD Alive(PoE Watchdog) \</li> <li>&gt; Long Distance PoE Transmission</li> <li>&gt; Smooth Transmission</li> <li>&gt; Wide Working Temperature: -10 to 55°C (14°F to 131°F)</li> <li>&gt; Port Isolation</li> </ul>	ریال ۱۵۰,۹۸۸,۰۰۰
94	DH-PFS3010-8ET-96	<ul style="list-style-type: none"> <li>- 8-Port PoE Switch (Unmanaged) . Layer two commercial switch</li> <li>• Supports PoE power management</li> <li>• Supports wall-mount installation . Supports anti-theft lock hole</li> <li>• MAC auto learning and aging, MAC address capacity is 16K</li> <li>• Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards</li> <li>• RJ45 port supports 10/100 Mbps self-adaptation</li> <li>• Supports 250 meters long distance PoE transmission</li> <li>• Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply</li> </ul>	ریال ۶۴,۹۰۰,۰۰۰
95	DH-PFS3106-4ET-60	<ul style="list-style-type: none"> <li>. 4-Port PoE Switch (Unmanaged)</li> <li>• Layer two Hardened PoE switch</li> <li>• Supports PoE power management</li> <li>• MAC auto learning and aging, MAC address capacity is 8K</li> <li>• Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply</li> <li>• Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards</li> <li>• Wide working temperature design: -30°C~ 65°C . Supports dual power backup</li> </ul>	ریال ۵۷,۷۰۰,۰۰۰

96

DH-PFS3102-1T

- 2-layer industrial level Ethernet media converter
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- 100M/1000M self-adaptive SFP fiber port
- Industrial wide temperature design



٢٦,٨٩٠,٠٠

97

DH-LR2218-16ET-240

- 16-Port ePoE Switch
- Supports long distance PoE transmission up to 800m with ePoE technology of Dahua
- Layer-two web managed ePoE switch
- Port 1-8 support three self-adaptive transmission modes which are IEEE, E100 and E10
- Port 1-8 support both twisted-pair transmission and coaxial cable transmission
- Support web management: port management, 802.1Q VLAN, STP/RSTP, LACP, 802.1X, QoS
- Support PoE management, Green PoE, Legacy Support
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards



٢٠٥,٢١٠,٠٠

98

DH-LR2110-8ET-120

- 8-Port ePoE Switch
- Supports long distance PoE transmission up to 800m with ePoE technology of Dahua
- Layer-two ePoE switch
- MAC auto study and aging, MAC address list capacity is 8K
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard
- Industrial wide temperature design
- Port indicator light is to display the status of current transmission mode for the port, which includes IEEE, E100 and E10



١٢١,٨٣٠,٠٠

99

DH-PFL2106-4ET-96

- 4-Port ePoE Switch
- Supports long distance PoE transmission up to 800m with ePoE technology of Dahua
- Two-layer industrial PoE switch
- MAC auto study and aging, MAC address list capacity is 8K
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard
- Industrial wide temperature design



٨٠,٧٧٠,٠٠

100

DH-NKB1000-E

- Keyboard to Control
- Dahua High Speed Dome • Dahua Standalone DVR
- Network Video Server Connection
- RS485, RS422 (reserved), USB, RS232 & Network Functions
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS or DSS platform via USB



١٦٩,٩٠٠,٠٠

101

DH-PFM900-E

- Integrated Mount Tester
- > 4.0" TFT screen, 800 × 480 resolution
- > H.264/H.265 decoding display for IPC
- > HDCVI/AHD/TVI/CVBS video display control
- > Support SD and HD direct switch
- > 12V/2A DC power supply for the camera
- > Support RS-485 control, and audio test
- > Length and attenuation tests of the network cable
- > Functions of digital multimeter



٤٨٣,٠٠٠,٠٠