

































مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 HAC-HFW1509MHP-A-LED-S2	<p>NEW</p> <p>5MP Full-color HDCVI Bullet Camera Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens Built-in Mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 120 dB true WDR, HLC,HLC-Pro, BLC, 3D DNR, AGC, AWB 2 LEDs 50m Distance, Smart Light, IP67, DC12V</p>		30,300,000
2 HAC-HFW1509TMP-IL-A	<p>NEW</p> <p>5MP Smart Dual Illuminators Bullet Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR. Smart Dual Illuminators, 40 m illumination distance Min. Illumination, 0.001 lux@F1.0 (Color, 30 IRE), 0.0001 lux@F1.0 (B/W, 30 IRE) Super Adapt, Built-in MIC, BLC; HLC; WDR; HLC-Pro 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable, IP67, 12 VDC</p>		35,800,000
3 HAC-HFW1509TLM-A-LED	<p>NEW</p> <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens Built-in Mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>		28,900,000
4 HAC-HFW1509TLM-LED	<p>NEW</p> <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>		27,200,000
5 HAC-HFW1509TP-LED	<p>NEW</p> <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>		26,800,000
6 HAC-HFW1509TP-A	<p>NEW</p> <p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) Built-in mic 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>		27,400,000
7 DH-HAC-HFW1500RP-Z-IRE6	<p>NEW</p> <p>5MP Starlight HDCVI IR Bullet Camera, Image Sensor 1/2.7 inch CMOS Max 25 fps@5MP (16:9 video output) CVI/CVBS/AHD/TVI switchable 2.7 mm-12 mm motorized lens, 0.005 Lux/F1.6, 30IRE, 0 Lux IR on Illumination Distance 60 m , S/N Ratio > 65 dB Pan/Tilt/Rotation Range Pan: 0°-360°, Tilt: 0°-90°, Rotation: 0°-360° Max. IR length 60 m, Smart IR, BLC/HLC/DWDR IP67, 12V DC</p>		36,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
8	DH-HAC-HFW1500THP-I4 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 40m, Smart IR, IP67, DC12V±30		18,100,000
9	DH-HAC-HFW1500THP-I8 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 80m, Smart IR, IP67, DC12V±30		20,700,000
10	DH-HAC-HFW1500TP-0360B-S3 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V		17,800,000
11	DH-HAC-HFW1500DP 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 80 m, Smart IR, IP67, DC12V		25,000,000
12	DH-HAC-HFW1500CMP 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V		17,800,000
13	HAC-B1A51 5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm, 2.8mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Plastic		13,600,000
14	DH-HAC-B2A51P 5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR IP67, DC12V, Casing Aluminium		15,900,000
15	DH-HAC-B1A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP,25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Plastic		11,500,000
16	DH-HAC-B2A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP,25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Aluminium		14,000,000
17	HFW1239TLMIP-IL-A 2MP Smart Dual Illuminators Bullet Camera Progressive CMOS - Focal Length 3.6 mm Max. 30 fps@1080p 0.001 lux@F1.6 (Color, 30 IRE) - 0.0001 lux(B/W, 30 IRE) - 0 lux (Illuminator on) Smart Dual Illuminators - Built-in-mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 130 dB true WDR, HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m distance - 2 IR Lights 40m distance Smart IR & WL, IP67, DC12V		22,700,000
18	HFW1239MHP-A-LED 2MP Full-color HDCVI Bullet Camera, 1/2.8" CMOS ,24/7 color imaging Max. 30 fps@1080p,3.6 mm fixed lens (6 mm optional) 50 m illumination distance , Super Adapt, 130 dB true WDR, 3D NR Focal Length 3.6 mm; 6 mm , Built-in mic ,CVI/CVBS/AHD/TVI switchable Min Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on , IP67, DC 12 V		25,800,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
19	<p>DH-HAC-HFW1239TLMP-A-LED</p> <p>2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 MP CMOS Minimum Illumination:0.005Lux/F1.6 1080@25fps, 720@25/50fps 3.6mm fixed lens Built-in mic CVI/CVBS/AHD/TVI Switchable WDR (130 db) , BLC, HLC, 2DNR,AGC,AWB Electronic Defog 40m LED distance, IP67, DC12V</p> <p>STARLIGHT Full-color </p>		20,600,000
20	<p>DH-HAC-HFW1239TLMP-LED</p> <p>2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS 0.005Lux/F1.6, 30IRE, 0Lux white Light on Max. 30fps@1080P 3.6mm fixed lens, 16x Digital Zoom CVI/TVI/AHD/CVBS Switchable, Support OSD Menu WDR (130 db)/E-Defog/BLC/HLC/AWB/AGC/2D DNR 40m LED Distance Smart Light, IP67, DC12V</p> <p>STARLIGHT Full-color</p>		20,300,000
21	<p>HAC-HFW1239TP-LED</p> <p>2MP Full-color HDCVI Bullet Camera 2MP 1/2.8" Progressive CMOS Max 2MP@25/30fps 3.6mm fixed lens CVI/CVBS/AHD/TVI switchable, Support OSD Menu WDR(130db), BLC, HLC, AWB, AGC, 3D DNR Smart Light, 1 LED 20m Distance, IP67, DC12V</p> <p>STARLIGHT Full-color</p>		19,500,000
22	<p>DH-HAC-HFW1231RP-Z-A</p> <p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable,Built in mic, WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V</p> <p>STARLIGHT </p>		33,300,000
23	<p>DH-HAC-HFW1231RP-Z-IRE6</p> <p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V</p> <p>STARLIGHT</p>		32,500,000
24	<p>DH-HAC-HFW1230RP-Z-IRE6</p> <p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.005Lux/F1.8 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable DWDR, BLC, HLC, 2DNR, AGC,AWB 60m LED distance, Smart IR, IP67, DC12V</p> <p>STARLIGHT</p>		29,500,000
25	<p>DH-HAC-HFW1230TP</p> <p>2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium</p> <p>STARLIGHT</p>		14,200,000
26	<p>DH-HAC-HFW1230TP-A</p> <p>2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Built-in mic DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p> <p>STARLIGHT</p>		14,600,000
27	<p>DH-HAC-HFW1230DP</p> <p>1/2.8" 2Megapixel CMOS (Starlight) 3.6mm Fixed lens, 25/30fps@1080P & @720P DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 80m, Smart IR, IP67, DC12V</p> <p>STARLIGHT</p>		18,800,000












توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
28	DH-HAC-HFW1220THP-I4 Value STARLIGHT 2MP Value Starlight HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Value Starlight Minimum Illumination:0.008Lux/F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D DNR Smart IR, Eletronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 40m, Smart IR, IP67, DC12V		14,600,000
29	HAC-HFW1209TLMP-LED-0360B Full-color NEW 2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3D DNR CVI/CVBS/AHD/TVI switchable, OSD Menu Support 40m LED distance, IP67, DC12V		15,700,000
30	HAC-HFW1209CMP-LED-0360B STARLIGHT Full-color NEW 2MP Full Color Starlight HDCVI Bullet CCTV Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS Max 30fps@2MP 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		14,700,000
31	HAC-HFW1209CP-LED-0360B Full-color NEW 2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V		12,300,000
32	DH-HAC-HFW1200RP-Z-IRE6 STARLIGHT NEW 2MP HDCVI IR Bullet Camera, 1/2.7 inch CMOS Max 30fps@1080P, Min Illumination 0.02Lux/F1.7, 30IRE, 0Lux IR on Motorized vari-focal 2.7 mm-12 mm, Fixed iris BLC/HLC/DWDR, Gain Control, Noise Reduction 2D NR, Smart IR Max. IR length 60m, IP67, DC12V Built-in mic(-A)		28,500,000
33	DH-HAC-HFW1200TLP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V 2MP HDCVI IR Bullet Camera		12,200,000
34	DH-HAC-HFW1200THP-A MIC 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional), Built-in mic HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR, IP67, DC12V 2MP HDCVI IR Bullet Camera		14,000,000
35	DH-HAC-HFW1200THP-I4 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Minimum Illumination:0.02Lux/F1.9 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart IR, Eletronic Defog HD and SD output switchable Max. IR length 40m, Smart IR, IP67, DC12V		13,750,000
36	DH-HAC-HFW1200DP-0360B-S5 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V		16,500,000
37	HAC-HFW1200CMP-0360B NEW 2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V		13,000,000











توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
38	HAC-HFW1200CMP-A NEW 2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens, Built-in mic CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V		14,000,000
39	DH-HAC-HFW1200SP HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		13,100,000
40	DH-HAC-HFW1200TP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 2.8mm/3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 25m, Smart IR, IP67, DC12V		13,600,000
41	DH-HAC-HFW1200TP-A NEW 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens, Built-in mic HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		14,000,000
42	DH-HAC-HUM3201B STARLIGHT 1/2.8" 2Megapixel CMOS(Starlight), 25/30fps@1080P & @720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR, DC12V		17,200,000
43	DH-HAC-B2A21P Cooper Series 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		10,650,000
44	DH-HAC-B1A21P Cooper Series 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Plastic		8,850,000
45	DH-HAC-HDW1509TP-IL-A NEW 5MP Smart Dual Illuminators Eyeball Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR Smart Dual Illuminators, 40 m illumination distance Super Adapt, Built-in MIC. 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable. IP67, 12 VDC.		33,900,000
46	DH-HDW1509TP-A-LED STARLIGHT Full-color NEW 5MP Full-color HDCVI Eyeball Camera Progressive CMOS - Focal Length 2.8 mm Min. Illumination 0.001 Lux/F1.0, 0 Lux warm light on illumination 2 LEDs Distance 40 m Built-in mic , CVI/CVBS/AHD/TVI switchable WDR 120db, BLC, HLC, HLC-Pro, AWB, AGC, 3DNR Privacy Masking, Smart Light, IP67, DC 12V		28,900,000
47	DH-HAC-HDW1509TLQP-A-LED NEW 5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V, Built-in mic		26,900,000
48	DH-HAC-HDW1509TLQP-LED Full-color 5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V		24,000,000
49	DH-HAC-HDW1500SLP 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		14,300,000
50	DH-HAC-HDW1500TRQP-A-0280B-S3 NEW 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP, 1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR,, Built-in Mic Max. IR LEDs length 20m, Smart IR, IP67, DC12V		17,200,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
51	<p>NEW</p> <p>DH-HAC-HDW1500TRQP-0280B-S3</p> <p>5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP,1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V</p>		15,400,000
52	<p>HAC-T2A51P</p> <p>Cooper Series</p> <p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium</p>		15,900,000
53	<p>HAC-T1A51P</p> <p>Cooper Series</p> <p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm and 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Plastic</p>		13,300,000
54	<p>DH-HAC-T2A41P</p> <p>Cooper Series</p> <p>1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, IP67, DC12V, Casing: Aluminium</p>		14,000,000
55	<p>DH-HAC-T1A41P</p> <p>Cooper Series</p> <p>1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, DC12V, Casing: Plastic</p>		11,500,000
56	<p>DH-HAC-HDW1239TLP-A-LED</p> <p>QUICK INSTALLATION</p> <p>STARLIGHT Full-color</p> <p>2M Full-color Starlight HDCVI Eyeball Camera 1/2.8 inch 2.16 Mega Pixels CMOS Minimum Illumination:0.005Lux/F1.6 Full-color starlight 1080@25fps, 720@25fps, 720@50fps 3.6 mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart Light, Electronic Defog HCVI/CVBS/AHD/TVI switchable Built-in Mic 20m LED distance, IP67, DC12V</p>		19,000,000
57	<p>DH-HAC-HDW1230MP</p> <p>STARLIGHT</p> <p>2MP Starlight HDCVI IR Eyeball Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p>		12,500,000
58	<p>NEW</p> <p>HAC-HDW1209TLQP-A-LED-0280B</p> <p>QUICK INSTALLATION</p> <p>Full-color</p> <p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens Built-in Mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		13,900,000
59	<p>NEW</p> <p>HAC-HDW1209TLQP-LED-0280B</p> <p>QUICK INSTALLATION</p> <p>Full-color</p> <p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		12,300,000
60	<p>DH-HAC-HDBW1200EP</p> <p>2MP HDCVI IR Dome Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm Fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V</p>		13,700,000
61	<p>DH-HAC-HDW1200LP</p> <p>QUICK INSTALLATION</p> <p>Full-color</p> <p>2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS Max 30fps@1080P, 2.1mm fixed lens HD and SD output switchable, Built in Mic, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR, IP67, DC12V</p>		16,300,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
62 DH-HAC-HDW1200MP	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V		11,700,000
63 DH-HAC-HDW1200EMP-A Metal Case	1/2.7" 2Megapixel CMOS , 25/30fps@1080P, Built-in MIC Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR 3.6 & 2.8mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V 2MP HDCVI Quick-to-install IR Eyeball Camera		14,500,000
64 HAC-HDW1200TRQP-A-0280B	1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens Built in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto switch by ICR Max. IR length 25m, Smart IR, IP50, DC12V 2MP HDCVI IR Eyeball Camera		12,200,000
65 DH-HAC-HDW1200TLP-A	1/2.7 inch CMOS Max 30fps@1080P 2.8mm Fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Built-in mic Electronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 30m, Smart IR, IP67, DC12V		12,900,000
66 DH-HAC-T2A21P Cooper Series	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		10,750,000
67 DH-HAC-T1A21P Cooper Series	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm & 3.6 fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V		8,650,000
68 DH-SD59225I-HC-S2	1/2.8" 2Megapixel Exmor R CMOS (Starlight) Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution 4.8mm ~ 120mm 25x optical zoom WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Control over coaxial cable 1-channel BNC HDCVI/CVBS output (switchable) Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 Alarm in/out, 1 Audio Input , RS485 IR Distance up to 150m, IP66,OSD		180,000,000
69 SD59230I-HC	2MP 30x Starlight IR PTZ HDCVI Camera, 1/2.8" Exmor R CMOS Max. 25/30fps @1080P(1920x1080) & 50/60fps @720Presolution 4.5mm~135mm 30x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Audio(in/out) 1 / 1 , Built-in 2/1 Alarm in/out IR Distance up to 150m, IP66,OSD		210,000,000
70 DH-SD49225I-HC-LA	2MP 25x Starlight IR PTZ HDCVI Camera, 1/2.8" STARVIS CMOS Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern HD and SD switchable, 2/1 Alarm In/Out 1CH Audio In, RS485, IR Distance up to 100m, IP66,OSD		168,000,000
71 DH-XVR1A04 Cooper Series	4CH Penta-brid 1080N/720P Real-Time Cooper Recorder H.264 video compression, 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support		19,750,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
72 XVR1B04-I	<p>Wiz Sense AI NEW</p> <p>4 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2MP(20 Mbps), 4CH: 1/4 Playback HDMI , VGA ,simultaneous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p> <p>Cooper Series</p>		22,750,000
73 DH-XVR1A08	<p>8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder H.264 video compression, 8CH:1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 MP(40 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output, 2*USB 2.0 10/100 Mbps LAN Interface, P2P Support</p> <p>Cooper Series</p>		24,300,000
74 XVR1B08-I	<p>Wiz Sense AI NEW</p> <p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), 4CH: 1/4/9 Playback HDMI , VGA ,simultaneous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p> <p>Cooper Series</p>		29,100,000
75 XVR1B08H-I	<p>Wiz Sense AI NEW</p> <p>8 Channels 5M-N/1080p Cooper 1U 1HDD Digital Video Recorder Supports Full-channel AI-Coding , H.265+/H.265 dual-stream Pentabrid (IP+CVI+AHD+TVI+CVBS) - Max 12 channels IP camera inputs Up to 8 channels SMD Plus Human/Vehicle Classification Encoding Capacity : 5M-N@(10 fps); 4M-N/1080p@(15 fps); 1080N@(25/30 fps) 1/4/8/9 Playback , 1 SATA port, up to 16 TB capacity 2*USB 2.0, Audio In/Out : 1/1 , 10/100 Mbps LAN Interface, P2P Support</p> <p>Cooper Series</p>		50,000,000
76 XVR5104HS-I3	<p>Wiz Sense AI NEW</p> <p>New GUI V4.0 Support - 4 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 6 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		37,800,000
77 XVR5104HS-4KL-I3	<p>Wiz Sense AI NEW 4K</p> <p>New GUI V4.0 Support - 4 Channel Penta-brid 4K WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		53,900,000
78 XVR5108HS-4KL(V.2)	<p>Wiz Sense AI</p> <p>New GUI V4.0 Support - 8CH Penta-brid 4K Recorder HDCVI 4K, AHD,5mp, HDTV 5MP 8+4ch support H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8MP Tripwire, Intrusion, Face Detection, Smart Search 1/1 Audio In/Out, 1 SATA Port , Up to 8TB 1*HDMI, 1*VGA ,simultaneous video Output 2*USB 2.0, 1*10/100 Mbps LAN Interface , P2P Support</p>		84,000,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
79	<p>NEW</p> <p>New GUI V4.0 Support - 8 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		57,300,000
80	<p>NEW</p> <p>4K</p> <p>New GUI V4.0 Support - 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9ch 1 SATA Port up to 10 TB capacity 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		95,500,000
81	<p>NEW</p> <p>New GUI V4.0 Support - 8 Channels Penta-brid 4K-N/5MP Encode Capacity All channel 4K@(7 fps); 6MP@ (10 fps); 5MP@ (12 fps); 4K-N/4 MP/3 MP@ (15 fps); 4M-N/1080P @ (25/30fps); AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS Up to 16 channels of IPC access / 128 Mbps Supports Full-channel AI Coding Perimeter Protection : 8 channels, 10 IVS for each channel / 2 channels (up to 12 face images/s) / Face Recognition : 2 channel up to 10 face databases / Full-channel SMD Plus Audio Input : 1, RCA (external) 8, BNC (coaxial) / Audio Output 1, RCA HDD Interface 1 SATA Port, up to 16TB RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 2A / Power Consumption Lower than 10 W / Operating Temperature -10 °C to +55 °C</p>		95,500,000
82	<p>Cooper Series</p> <p>16CH Penta-brid 1080N/720P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression 1st channel 1080N/720P@25fps, others 1080N/720P@15fps 16CH: 1/4/9/16 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 MP(64 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 2 USB 2 , 10/100 Mbps LAN Interface, P2P Support</p>		48,000,000
83	<p>NEW</p> <p>Wiz Sense AI</p> <p>Cooper Series</p> <p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6MP(64 Mbps) 4CH: 1/4/9/16 Playback HDMI/VGA Simultaneous Video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p>		54,500,000
84	<p>NEW</p> <p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 1 SATA Port up to 10 TB capacity 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		97,000,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
85	<p>NEW</p> <p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P XVR 5MN, 4M-N, 1080P, 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+8 IP up to 5MP(96 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 1 SATA Port, up to 8TB capacity 1 USB 2.0 , 1 USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support Tripwire, Intrusion, Face Detection</p>		86,700,000
86	<p>NEW</p> <p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS/IP video inputs Max 24 channels IP camera, up to 6MP; Max 128Mbps incoming bandwidth Supports Full-channel AI Coding / 16 channel SMD / 2 channel face recognition Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA HDD Interface 1 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature -10 °C to +55 °C</p> <p>WizSense AI</p>		97,000,000
87	<p>New GUI V4.0 Support - 16CH Penta-brid 5MN/4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder, 5MN/4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 MP(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB HDMI , VGA ,simultanous video Output, RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface, P2P Support</p>		112,500,000
88	<p>NEW</p> <p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p> <p>WizSense AI</p>		126,000,000
89	<p>NEW</p> <p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 16+8 channels, each IP Channel up to 6MP Supports Full-channel AI Coding Perimeter Protection : 2 channel, 10 IVS for each channel / Face Detection : 6 attributes , 2 channels each channel up to 12 faces / Face Recognition : 2 channel up to 10 face databases / Full-channel SMD Plus Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature -10 °C to +55 °C</p> <p>WizSense AI</p>		126,000,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
90 XVR5216AN-4KL-I2	<p>NEW</p> <p>4K</p> <p>WizSense AI</p> <p>New GUI V4.0 Support - 16 Channel Penta-brid 4K/5MP WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		193,000,000
91 DH-XVR5216AN-4KL	<p>NEW</p> <p>4K</p> <p>New GUI V4.0 Support - 16 Channel Embedded Processor 16+8 Channel, each channel up to 8M HDCV 4K, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/ Record rate Main stream: 4K(1~7fps);4MP(1~15fps);1080P (1~25/30f) H.264+/H.26 dual-stream video compression Internal HDD 2 SATA Ports, up to 8TB capacity for each IP Camera Input 8+4/16+8 Channel, each channel up to 8 Audio In/Out 1/1, RC - 2 USB Ports (1 USB 2.0, 1 USB 3), 1*RS485, 1*1000 Mbps</p>		169,000,000
92 DH-XVR5216AN-4KL-I3	<p>NEW</p> <p>WizSense AI</p> <p>New GUI V4.0 Support - 16 Channels Penta-brid 4K-N/5MP Encode Capacity All channel 4K@(7fps); 6MP@(10fps); 5MP@(12fps); 4K- N/4MP/3MP@(15fps); 4M-N/1080P(25/30fps); AI Coding: H.265+, H.265; H.264+, H.264 Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 8MP Supports Full-channel AI Coding Perimeter Protection : Advanced Model: 2 channels , General Model: 8 channels ; Face Detection : 2 channels ;Face Recognition : 2 channels , Up to 10 face databases , SMD Plus : 16 channels Audio Input :1-channel RCA , 16-channel BNC 16 / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 12 VDC, 5A / Power Consumption Lower than 15 W(without HDD) / Operating Temperature-10 °C to +55 °C</p>		193,000,000
93 DH-XVR5232AN-S2(V.2)	<p>New GUI V4.0 Support - 32CH Penta-brid 1080P Recorder 4M-N/1080P@15fps, 1080N/720P@25fps H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 MP(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		181,000,000
94 XVR5232AN-I2	<p>NEW</p> <p>WizSense AI</p> <p>New GUI V4.0 Support - 32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		208,000,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
95 XVR5232AN-I3	<p>NEW</p> <p>New GUI V4.0 Support - 32 Channels Penta-brid 5M-N/1080P Encode Capacity All channels 5M-N@(10fps); 4M-N/1080P@(15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 32 IP channels, up to 6MP / bandwidth: 128 Mbps Supports 16-channel AI Coding Perimeter Protection : Up to 4 channels 10 IVS for each channel / Face Detection :2 channels (up to 12 face images/s) / Face Recognition : Up to 2 channels, Up to 10 face databases /16 channels SMD Plus) Audio Input : 1, RCA (external) 32, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 5A / Power Consumption Lower than 17 W / Operating Temperature -10 °C to +55 °C</p>		208,000,000
96 XVR5432L-I3	<p>NEW</p> <p>32 Channels Penta-brid 5M-N/1080P 4HDDs WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. Supports 16-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera, each channel up to 8MP; 128 Mbps bandwidth. Up to 8 channels video stream (analog channel) perimeter protection. Up to 16 channels video stream (analog channel) SMD plus. Up to 2 channels video stream (analog channel) human face recognition. Perimeter Protection, Face Detection, Face Recognition : Up to 10 face databases with 10,000 face images, SMD Plus Multi-screen Display 1/4/8/9/16/25/36 IoT & POS functionalities.</p>		345,000,000
97 DH-XVR4232AN-I	<p>NEW</p> <p>32 Channels Penta-brid 1080N/720P 1U 2HDDs WizSense Digital Video Recorder Video Compression AI Coding; H.265+; H.265; H.264+; H.264 Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth. Multi-screen Display 1/4/8/9/16/25/36 Audio Input 1-channel RCA (external) 32-channel BNC (coaxial audio) Two-way Talk, HDD Interface 2 SATA ports, up to 16 TB Up to 16 channels video stream (analog channel) SMD Plus. Long transmission distance over coax cable.</p>		140,000,000

