











مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 PSD81602-A360	<p>8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10</p>		Call
2 PSD8802-A180	<p>4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10</p>		Call
3 PFW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
4 PFW8601-A180	<p>3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens, Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
5 PDBW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
6 ITC237-PW1B-IRZ	<p>دوربین ANPR با قابلیت تشخیص پلاک مناسب برای ورودی های پارکینگ 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database,1 ch relay out to control the barrier performance for outdoor applications 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264 dual-stream encoding 25/30fps@1080P(1920x1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE</p>		165,000,000
7 IPC5831EP-ZE	<p>1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) 2.7mm ~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE (Tripwire Intrusion Object Abandoned/Missing Face)</p>		12,400,000













ردیف	مدل	مشخصات فني	تصوير	قيمت (ريال)
8	IPC-HFW2831T-ZAS-S2 	NEW 8MP Lite IR Vari-focal Bullet Network Camera 8MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.5 high image definition 8MP@15fps & 4MP@25/30fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+, (MJPEG in Sub Stream) IVS Intrusion, Tripwire Micro SD 256GB, 1ch Audio I/O, 1ch Alarm I/O WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T		99,000,000
9	HF2831T-ZS-S2 	8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm-13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire Intrusion)		98,000,000
10	IPC-HFW2831TP-AS-S2 	NEW 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps Smart H.265+/ Smart H.264+, H.265; H.264; H.264B; MJPEG (only supported by the sub stream) Built-in IR LED, max IR distance: 80m, 3.6mm Fixed Lens Min. Illumination 0.009 Lux@F2.0 ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec WDR(120db), 3D NR, HLC, BLC, AGC, AWB, ROI, Smart IR Intrusion, tripwire Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE power support supply, IP67, IK10		73,000,000
11	IPC-HFW2831S-S2 	8MP Lite IR Fixed-focal Bullet Network Camera 1/2.7" Progressive CMOS image sensor, low illuminance, high image definition Illumination 0.009 Lux@F2.0 SMART H.264+/H.265+, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps WDR (120 db), 3D DNR, HLC, BLC, AGC, AWB, ROI, Smart IR Intrusion, tripwire, SD Card 256GB, IP67, PoE		67,000,000
12	IPC-HFW1830SP-0360B-S6 	8MP 8MP 1/2.7" CMOS Entry IR Fixed-focal Bullet Network Camera Outputs max. 8MP@15fps, supports 2688 × 1520 (2688 × 1520) @25/30 fps Illumination 0.004 Lux@F2.0 (B/W, 30 IRE) H.265+&H.264+ high compression rate, and ultra-low bit rate. WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Built-in MIC 3.6mm fixed lens, Built-in IR LED, and the max. illumination distance is 30 m. 12 V DC/PoE power supply, IP67		58,000,000
13	HF2531TP-ZS 	1/2.7" 5Megapixel progressive CMOS 2.7-13.5mm Motorized lens 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB, Max IR LEDs Length 60m , Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)		86,000,000
14	DH-IPC-HFW5449T1-ZE-LED  	NEW 4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 × 1520) @30 fps, Focal Length 2.7 mm-12 mm Min. Illumination 0.0005 Lux@F1.0 , S/N Ratio > 56 dB Built-in warm illuminator, and the max. illumination distance : 70 m ROI, SMART H.264+/H.265+, flexible coding, WDR 140db , 3D NR, HLC, BLC IVS (Perimeter Protection) : Tripwire; intrusion; fast moving, loitering detection, people gathering; parking detection, Face Detection, People Counting, Intelligent Search Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0		165,000,000
15	HF25442EP-ZE-0832   	4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688×1520), 50/60fps@2Mp(1920 × 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lenz, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE		140,000,000









<p>NEW</p> <p>16 IPC-HFW5241E-Z5E</p>   	<p>2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8" Progressive STARVIS™ CMOS low illuminance 0.0015 Lux@F1.3 high image definition 2MP@25/30fps 7-35mm Motorized Lens SMART H.264+/H.265+ IVS: Tripwire; intrusion; fast moving (with accurate classification of vehicle and human); loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS, Defog, 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T</p>	 <p>122,000,000</p>
<p>17 DH-IPC-HFW4431TP-S-54</p>	<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>	 <p>55,200,000</p>
<p>NEW</p> <p>18 DH-IPC-HFW3849T1-AS-PV-S3</p>  	<p>8MP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8 MP (3840 x 2160)@25/30 fps Min. illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm illuminator, and the max. illumination distance: 30 m Intrusion, tripwire (support the classification and accurate detection of vehicle and human) WDR 120db, 3D NR, HLC, BLC, digital watermarking, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256G SD card; built-in dual MICs; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0, One-click arming/disarming through alarm input</p>	 <p>118,000,000</p>
<p>NEW</p> <p>19 DH-IPC-HFW3449EP-AS-LED-3.6</p> 	<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>	 <p>66,300,000</p>
<p>20 DH-IPC-HFW3449EP-AS-LED-2.8</p> 	<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688x1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>	 <p>66,300,000</p>
<p>21 HFW3441TP-ZS-27135</p>  	<p>4MP IR Vari-focal Bullet WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688x1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>	 <p>93,000,000</p>
<p>NEW</p> <p>22 DH-IPC-HFW2449S-S-IL</p>  	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 x 1520)@20 fps, and supports 2560 x 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.</p>	 <p>49,500,000</p>

ردیف	مدل	مشخصات فني	تصوير	قيمت (ريال)
23	DH-IPC-HFW2441T-ZS	<p>NEW</p> <p>4MP IR Vari-focal Bullet WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440, (2560 × 1440)@25/30 fps Min. illumination, 0.008 lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm–13.5 mm Built-in IR LED, and the max. illumination distance is 60 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports), audio: 1 in, 1 out (Only - ZAS supports), 256G SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67, IK10 (optional) protection, SMD Plus</p>		84,000,000
24	IPC-HFW24395P-SA-LED-0360B-S2	<p>NEW</p> <p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		46,200,000
25	HFW2431TP-AS-S2	<p>NEW</p> <p>4MP Lite IR Fixed-focal Bullet Network Camera, 1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520) @20 fps, and supports 2560×1440 (2560 × 1440) @25/30 fps Built-in IR LED, max IR distance: 80 m, Intelligent detection: Intrusion, tripwire H.265; H.264; H.264B; MJPEG(only supported) WDR(120 dB), 3D NR, HLC, BLC, digital watermarking Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE , IP67 protection, IK10 protection (optional)</p>		56,500,000
26	HFW2431TP-ZS-S2	<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. illumination: 0.008 Lux@F1.5, 2.7–13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 60 m, Smart IR, IP67, PoE</p>		73,500,000
27	IPC-HFW1431S1-S4-S5	<p>NEW</p> <p>4MP Entry IR Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart H.265+/H.264+ WDR(120db), ROI, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)</p>		31,500,000
28	HFW1431SP-0360B-S4	<p>4MP Entry IR Fixed-focal Bullet Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. illumination: 0.03 Lux@F2.0, 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance: 30 m, Smart IR, IP67, PoE</p>		37,000,000
29	HFW3541EP-AS	<p>NEW</p> <p>5MP IR Fixed focal Bullet WizSense Network Camera 1/2.7" CMOS image sensor, Outputs max. 5MP (2592 × 1944) @20 fps H.265 codec SMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking, Min illumination 0.0005 Lux@F1.6 (B/W, 30IRE) 12V DC/POE IP67 SMD Plus Supports max. 256 G Micro SD card, built-in Mic</p>		Call
30	IPC-HFW3549T1P-AS-PV	<p>NEW</p> <p>5-MP 1/2.7" CMOS image sensor, low luminance, Smart Dual Illumination Min. illumination : 0.003 lux@F1.0 (Color, 30 IRE) / 0.0003 lux@F1.0 (B/W, 30 IRE) / 0 lux (illuminator on) Lens Fixed-focal 3.6 mm , 15.6 m Recognize & 7.8 m Identify, Illumination Distance : 30 m (2 IR LED) / 30 m (2 warm light) AI H.265, AI H.264 , Smart H.265+, Smart H.264+, Built-in MIC Main stream: 2880 × 1620 or 2960 × 1668 @20fps / 2688 × 1520 @ (30 fps) WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination, Defog, Scence Self-adaption Storage : FTP, SFTP, Micro SD card (support max. 256 G), NAS ROM : 128MB, RAM : 512MB, S/N Ratio > 56db , Sound and Light Alarm, Active Deterrence, IVS (Tripwire, intrusion), SMD 4.0, Smart Search, Quick Pick, AI SSA Audio In/out : 1/1 , Alarm in/out : 1/1, RJ-45 (10/100 Base-T) , 3.3 W (12 VDC); 4.4 W (PoE), IP67</p>		99,500,000
31	HFW3549EP-AS-LED-0360B	<p>NEW</p> <p>5MP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera 5MP, 1/2.7" CMOS image sensor low illuminance 0.003 Lux@F1.0 SMP@20 fps, 4MP@25/30 fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, Built-in warm light, max. illumination distance: 30 m, Onvif Profile S/G/T</p>		73,500,000









مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
32	<p>IPC-HFW3541TP-ZS-27135</p> <p>STARLIGHT Wiz Sense</p> <p>5MP IR Vari-focal Bullet WizSense Network Camera 5MP, 1/2.7" Progressive CMOS 0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on) high image definition 5MP@20fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ 3 Streams IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		111,000,000
33	<p>IPC-HFW2531TP-AS-S2</p> <p>STARLIGHT</p> <p>5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.6 high image definition 5MP@20fps, 3.6mm fixed Lens SMART H.264+/H.265+, IVS Intrusion/Tripwire 1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T</p>		64,800,000
34	<p>HFW2431SP-S-S2</p> <p>STARLIGHT</p> <p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE</p>		42,500,000
35	<p>HFW2249SP-S-IL-0360B</p> <p>Full-color STARLIGHT Wiz Sense</p> <p>NEW</p> <p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE) Outputs max. 2 MP (1920 x 1080)@25/30 fps, Fixed Lens 3.6mm Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B Built-in warm light/IR LED : 30m/30m ROI, WDR, 3D NR, HLC, BLC, digital watermarking SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC. 12 VDC/PoE power supply, easy for installation, IP67</p>		41,000,000
36	<p>HFW2249SP-S-IL-0280B</p> <p>Full-color STARLIGHT Wiz Sense</p> <p>NEW</p> <p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE) Outputs max. 2 MP (1920 x 1080)@25/30 fps, Fixed Lens 2.8mm Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B Built-in warm light/IR LED : 30m/30m ROI, WDR, 3D NR, HLC, BLC, digital watermarking SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC. 12 VDC/PoE power supply, easy for installation, IP67</p>		41,000,000
37	<p>HFW2231SP-S-0360B-S2</p> <p>STARLIGHT</p> <p>2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 x 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		31,000,000
38	<p>HFW2230SP-S</p> <p>STARLIGHT</p> <p>2MP IR Bullet Network Camera 1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire Intrusion)</p>		30,000,000
39	<p>IPC-HFW2239SP-SA-LED-S2</p> <p>Full-color STARLIGHT</p> <p>NEW</p> <p>2MP Lite Full-color Fixed-focal Bullet Network Camera 1/2.8" CMOS image sensor,Outputs max. 2MP (1920 x 1080) @25/30 fps ROI, SMART H.264+/H.265+, flexible coding, Min Illumination 0.0017 Lux@F1.0 Intelligent detection: Intrusion, tripwire WDR(120db), 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card and built-in Mic,12V DC/PoE ,IP67</p>		37,500,000
40	<p>IPC-HFW2231T-ZS-S2</p> <p>STARLIGHT</p> <p>NEW</p> <p>2MP Lite IR Vari-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS, low illuminance 0.002 Lux@F1.5 high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card 256 GB WDR(120db), Rol, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		65,000,000
41	<p>HFW1530SP-0360B-S6</p> <p>STARLIGHT</p> <p>NEW</p> <p>5MP 1/2.7" CMOS image sensor Outputs max. 5MP (2880 x 1620) @20 fps,Fixed-focal 3.6mm min illumination 0.003 Lux@F2.0 (B/W, 30 IRE) H.265 codec, SMART H.264 +/H.265+ Built-in IR LED, and the max. illumination distance is 30 m Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC, IP67,POE</p>		39,800,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
42	<p>NEW</p> <p>DH-IPC-HFW1239S1-LED-S5</p> <p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T</p> <p>Full-color</p>		26,400,000
43	<p>NEW</p> <p>HFW1230T1P-ZS</p> <p>2MP Entry, 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 2MP (1920 × 1080)@25/30 fps. Min. Illumination : 0.008 Lux@F1.7 (Color, 30 IRE), 0.0008 Lux@F1.7 (B/W, 30 IRE) Motorized vari-focal, 2.8 mm–12 mm, IR Distance 50 m(2 IR) Smart H.265+, Smart H.264+, H.265 codec, high compression rate, ultra-low bit rate. DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination, S/N Ratio > 56 dB 1 Port RJ-45 (10/100 Base-T), 12V DC/PoE (802.3af), IP67, Humidity ≤95%</p>		52,000,000
44	<p>NEW</p> <p>HFW1230S1P-0360B-S5</p> <p>2MP Entry IR Fixed-Focal Bullet Network Camera 1/2.8" CMOS image sensor, low illuminance Fixed Lens 3.6mm, F2.0, Horizontal: 84° Outputs max. 2MP (1920 × 1080) @25/30 fps Smart H.265+, Smart H.264+, H.265, H.264, H.264B ONVIF (Profile S/Profile T) Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, DWDR, 3D NR, HLC, BLC, digital watermarking 2V DC/PoE power supply, IP67</p>		24,000,000
45	<p>HFW1230SP-S4-S5</p> <p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30m, Smart IR IP67, PoE</p>		27,000,000
46	<p>HDW4431EMP-AS-S4</p> <p>4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p> <p></p>		48,000,000
47	<p>NEW</p> <p>HDBW3441EP-AS</p> <p>4MP IR Fixed focal Dome WizSense Network Camera 1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520)@30 fps H.265 codec, SMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking Supports max. 256 G Micro SD card, 12V DC/POE, IP67, IK10, SMD Plus Min illumination 0.0005 Lux@F1.6 (B/W, 30IRE) Audio Input 1 channel (RCA port), Audio Output 1 channel (RCA port) Alarm Input 1 channel in, Alarm Output 1 channel out</p> <p>STARLIGHT Wiz Sense</p>		57,000,000
48	<p>HDW3441TMP-AS-0280B</p> <p>4MP IR Fixed focal Eyeball WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p> <p>STARLIGHT Wiz Sense</p> <p></p>		54,000,000
49	<p>NEW</p> <p>HDBW2831EP-S-S2</p> <p>1/2.7" 8Megapixel progressive CMOS Min. Illumination:0.009 Lux@F2.0 3.6mm Fixed Lens max. 8MP (3840 × 2160) @15 fps, 2688×1520 (2688 × 1520) @25/30 fps SMART H.264+/H.265+, flexible coding IVS(Tripwire; intrusion), Abnormality detection: Motion detection, video tampering WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Built-in IR LED Max.Length 30m, IP67, PoE</p> <p>STARLIGHT Wiz Sense</p>		69,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
50	<p>HDBW2531RP-ZAS</p> <p>STARLIGHT</p> <p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Mirco SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67,IK10, PoE</p>		86,000,000
51	<p>IPC-HDBW2531E-S-S2</p> <p>STARLIGHT</p> <p>NEW</p> <p>SMP Lite IR Fixed-focal Dome Network Camera SMP, 1/2.7" Progressive CMOS Min. Illumination 0.008 Lux @ F1.6 Max 5MP@20fps SMART H.264+/H.265+ IVS: Intrusion, tripwire Mirco SD card 256GB WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol max IR distance: 30m, 12V DC, PoE, IP67,IK10</p>		43,200,000
52	<p>IPC-HDW2831TP-AS-S2</p> <p>STARLIGHT</p> <p>NEW</p> <p>8MP Lite IR Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensorOutputs max. 8MP (3840 × 2160) @15 fps Min Illumination 0.009 Lux@F2.0 Built-in IR LED, max IR distance: 30 m SMART H.264+/H.265+ WDR, 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card, built-in MIC 12V DC/PoE,IP67</p>		70,000,000
53	<p>DH-IPC-HDW2449T-S-IL</p> <p>WizSense Full-color STARLIGHT</p> <p>NEW</p> <p>4MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human Supports max. 256 G Micro SD card; built in MIC, 12 VDC/PoE power supply, easy for installation, IP67 protection,SMD Plus</p>		51,000,000
54	<p>IPC-HDW2439TP-AS-LED-0360B</p> <p>STARLIGHT Full-color</p> <p>NEW</p> <p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		47,200,000
55	<p>IPC-HDW2439TP-AS-LED-0280B-S2</p> <p>STARLIGHT Full-color</p> <p>NEW</p> <p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		47,200,000
56	<p>DH-IPC-HDBW2441E-S</p> <p>STARLIGHT WizSense</p> <p>NEW</p> <p>4MP 1/2.9" CMOS image sensor, IR Fixed-focal Dome WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2566 × 1440@25/30 fps Min. Illumination 0.008 lux@F1.6 (Color,30IRE), 0.0008 lux@F1.6 (B/W,30IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, , WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67, IK10 protection, SMD Plus</p>		46,800,000
57	<p>DH-IPC-HDBW2441R-ZS</p> <p>STARLIGHT WizSense</p> <p>NEW</p> <p>4MP IR Vari-focal Dome WizSense Network Camera, 4-MP 1/2.9" CMOS image sensor Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 , (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) , 0.0008 lux@F1.5 (B/W, 30 IRE) , 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance : 40 m, ROI, SMART H.264+/H.265+ WDR 120dB, 3D NR, HLC, BLC, Focal Length 2.7 mm~13.5 mm Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); 256G SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67 and IK10 protection, SMD Plus</p>		79,500,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
58	HDBW2431RP-ZS-27135-S2	<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>		72,000,000
59	HDBW2431RP-ZAS-S2	<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>		73,000,000
60	HDBW2431EP-S-0360B-S2	<p>4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE</p>		41,000,000
61	HDBW2431EP-S-0280B-S2	<p>NEW 4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 2.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE</p>		41,000,000
62	HDW2431TP-AS-0280B-S2	<p>NEW 4MP Lite IR Fixed-focal Eyeball Network Camera 1/3" CMOS image sensor, Outputs 4MP (2560 × 1440)@25/30 fps H.265 coding, SMART H.264+/H.265+, Fixed Lens 2.8mm Min. Illumination 0.008 Lux @ F1.6 WDR(120db), 3D NR, HLC, BLC, digital watermarking, Intelligent detection: Intrusion, tripwire Max. 256 GB SD card and built-in Mic, 12V DC/POEIP67</p>		43,200,000
63	HDW2431TMP-AS-0280B-S2	<p>4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE</p>		44,000,000
64	HDBW1431EP-0280B-S4	<p>NEW 4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Network, low illuminance Min. Illumination : 0.03 Lux @ F2.0 ,Illumination Distance : 30 m(3 IR LED), S/N Ratio > 56db Lens Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° / Diagonal: 111° Smart H.265+, H.265, Smart H.264+, H.264 Main Stream: 2688 × 1520 (20 fps), high compression rate, ultra-low bit rate WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination Storage(FTP, SFTP, NAS) , ROM : 128MB, RAM : 512MB 12V DC/POE (802.3af), Power Consumption < 5.5W, 1 port RJ-45 (10/100 Base-T) ,IP67, IK10</p>		37,500,000
65	HDW1431TP-A-0360B-S4	<p>NEW 4MP Entry IR Fixed-focal Eyeball Network Camera 1/3" 4Megapixel progressive CMOS, Fixed-focal 3.6mm 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), Image flip, 3D DNR, HLC, BLC, digital watermar Support ROI,Built-in MIC Max. IR LEDs Length 30m, IP67, PoE</p>		37,200,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
66	HDW1431T1P-0280B-S4-S5	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE		34,000,000
67	DH-IPC-HDW2249TP-S-IL-0280B	NEW 2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance Min. Illumination : 0.0002 lux@F1.6 (B/W, 30 IRE) , Fixed Lens 2.8 mm Outputs max. 2 MP (1920 × 1080)@25/30 fps Smart Codec : Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B SMD Plus, intrusion, tripwire (accurate detection of vehicle and human). Supports max. 256G Micro SD card, built in MIC . ROI, WDR, 3D NR, HLC, BLC, digital watermarking Built-in warm light/IR LED : 30m/30m 12 VDC/PoE power supply, easy for installation, IP67		41,000,000
68	HDW2231TMP-AS-S2	2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Roi Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		35,000,000
69	IPC-HDW2231TP-AS-0280B-S2	NEW 2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		34,500,000
70	IPC-HDW2230T-AS-S2	NEW 2MP IR Eyeball Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005 Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		30,000,000
71	IPC-HDBW2230E-S-S2	NEW 2MP Lite IR Fixed-focal Dome Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm Fixed Lens SMART H.264+/H.265+ IVS Tripwire; intrusion Micro SD 256GB DWDR, 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T		29,800,000
72	HDW1530TP-0280B-S6	NEW 5MP Entry IR Fixed-focal Eyeball Network Cam 1/2.7" CMOS image sensor low illuminance 0.003 Lux @F2 Outputs max. 5MP (2880 × 1620) @20 H.265 code, SMART H.264 +/H.265 DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC,12 V DC/PoE power supply		40,500,000
73	DH-IPC-HDW1239T1-A-LED-S5	NEW 2MP Lite Full-color Fixed-focal Eyeball Network Camera Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination : 0.005 Lux @F1.6, Built-in LEDs, max LED distance: 15 m, built in MIC ROI, SMART H.264/H.265, flexible coding, applicable to various Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, 12V DC/PoE power support, IP67 protection		29,500,000
74	DH-IPC-HDW1239T1-LED-0360B-S5	NEW 2 MP Entry Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T		26,400,000





















<p>75</p> <p>DH-IPC-HDW1239T1P-LED-0280B-S5</p> <p>STARLIGHT Full-color</p>	<p>NEW</p> <p>2 MP Entry Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>		<p>26,400,000</p>
<p>76</p> <p>DH-IPC-HDW1230T1-A-S5</p> <p>STARLIGHT</p>	<p>NEW</p> <p>2MP Entry IR Fixed-Focal Eyeball Network Camera Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate, Min. Illumination : 0.01 Lux @F2.0 Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various, built in MIC Rotation mode, DWDR, 3D NR, HLC, BLC, S/N Ratio 56 dB, digital watermarking 12V DC/PoE power supply, IP67 protection</p>		<p>27,800,000</p>
<p>77</p> <p>HDW1230T1P-0280B-S5</p>	<p>2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0, 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR, IP67, PoE</p>		<p>24,000,000</p>
<p>78</p> <p>HDBW1230EP-0360B-S2</p>	<p>1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE</p>		<p>27,000,000</p>
<p>79</p> <p>DH-SD29204T-GN</p>	<p>1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion Scene Change Face Abandoned-Missing Object)</p>		<p>72,500,000</p>
<p>80</p> <p>DH-SD1A203T-GN</p> <p>STARLIGHT</p>	<p>STARLIGHT</p> <p>1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned Missing Face Detection)</p>		<p>74,000,000</p>
<p>81</p> <p>SD3A205-GNP-PV</p> <p>Wiz Sense</p>	<p>NEW</p> <p>2MP Starlight IR AI WizSense Network PTZ Camera H.265; H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream); H.265+; H.264+ Focal Length 2.7 mm~13.5 mm, Optical Zoom 5x Tripwire and intrusion, Deep-learning-based perimeter protectionm SMD Plus IR distance up to 30m Starlight technology Up to 300 presets DWDR, HLC, BLC, AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), ROI, Defog Built-in Mic, Built-in Speaker, Two Way Audio ONVIF Profile S&G&T; CGI IP66; TVS 2000V lightning proof; surge protection; voltage transient protection</p>		<p>96,500,000</p>
<p>82</p> <p>DH-SD6CE230U-HNI</p> <p>STARLIGHT</p>	<p>1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking,Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10</p>		<p>340,000,000</p>










ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
83	DH-SD6CE245XA-HNR	<p>2MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), 2D/3D DNR, BLC, HLC, AGC, AWB Auto-tracking, Perimeter protection, Face detection, SMD Plus Tripwire and intrusion, alarm triggering by target types (human and vehicle) Support Defog, ROI Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10</p>		480,000,000
84	DH-SD6CE245U-HNI	<p>2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10</p>		Call
85	SD5A245XA-HNR	<p>NEW</p> <p>2MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265; H.265+; H.264+; H.264; MJPEG (Sub Stream) Max. 50/60 fps@1080P Pan/Tilt Range Pan: 0°~360°; Tilt: -15°~+90° Manual Control Speed Pan: 0.1°/s~240°/s; Tilt: 0.1°/s~120°/s WDR(120db), HLC, BLC, 2D/3D DNR, Rol, EIS, Defog, AWB, AGC, Privacy Masking, Day/Night Auto Auto Tracking, SMD Plus, Intrusion, Tripwire, Object Abandoned/Missing, Face Detection Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm I/O 2/1, Audio I/O 1/1, Supports Two Way Talk Focal Length 3.95 mm~177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux (IR on) IR distance up to 150 m, 45x optical zoom ONVIF Profile S&G&T, DC 24V/2.5A ± 25%; PoE+ (802.3at), Operating Temperature -40°C to +70°C IP67; IK10; TVS 6000V lightning protection; surge protection; voltage transient protection</p>		470,000,000
86	DH-SD5A232XB-HNR	<p>NEW</p> <p>2MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS 32x optical zoom,Max. 50/60 fps@2M Min Illumination Color: 0.005 lux@F1.6,Focal Length 4.8 mm~154 mm Smart H.265+; H.265; Smart H.264+; H.264B Face detection ,tracking and perimeter protection,SMD PLUS IR distance up to 150 m,PoE+, IP67, IK10 WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC</p>		407,000,000
87	DH-SD5A232XA-HNR	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.9mm~156mm 32x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR(2D/3D), BLC, HLC Support Defog, ROI, Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 2/1 in/out, Audio 1/1 in/out IR Distance up to 150m, PoE+, IP67, IK10</p>		407,000,000
88	DH-SD49425ZB-HNR	<p>NEW</p> <p>4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor: 1/2.8" STARVIS™ CMOS 1/2.8" 4Megapixel CMOS, Powerful 25x optical zoom, ROM: 4GB, RAM: 1GB Starlight technology, Max.25/30fps@4M, Illuminator Number: 4 Focal Length: 4.8 mm~120 mm, Field of View: H: 60.0°~2.5°; V: 30.8°~2.2°; D: 66.7°~2.9° Min. Illumination: Color: 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6: 0Lux@F1.6 (IR light on) Illuminator On/Off Control: Zoom Prio/Manual/SmartIR Perimeter protection, Face Detection, Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC, AGC, ANR, ROI, Electronic Defog Pan: 0.1°~200°/s, Tilt: 0.1°~120°/s, Presets: 300, Tour: 8 (up to 32 presets per tour), Pattern: 5, Scan: 5 IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/1</p>		267,000,000

<p>89 SD49425XB-HNR</p> <p>STARLIGHT</p>	<p>Wiz Sense</p> <p>4MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" STARVIS™ Progressive CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max.25/30fps@4M, 960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>	 <p>267,000,000</p>
<p>90 SD49225XA-HNR-S3</p> <p>STARLIGHT</p>	<p>NEW</p> <p>2MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS , 25x optical zoom, Min Illumination Color: 0.005 lux@F1.6 Max. 25/30 fps@1080p IR distance up to 100 m , Perimeter protection,Face detection,SMD Plus,IP66 Pan: 0° to 360° endless ,Tilt: -15° to +90°, auto flip 180° , Pan: 200°/s; Tilt: 100°/s Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream) Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC</p> <p>STARLIGHT Wiz Sense</p>	 <p>220,000,000</p>
<p>91 SD49225XA-HNR</p> <p>STARLIGHT</p>	<p>Wiz Sense</p> <p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p> <p>STARLIGHT Wiz Sense</p>	 <p>220,000,000</p>
<p>92 SD49225ZB-HNR</p> <p>STARLIGHT</p>	<p>NEW</p> <p>1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm–120 mm Max. 25/30 fps@1080p - Min. Illumination Color: 0.005 lux@F1.6 / B/W: 0.0005 lux / 0 lux (IR light on) IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+; H.265; Smart H.264+ WDR(120dB),DNR(2D/3D), BLC, HLC, AWB, AGC , RoI , Electronic Defog IR distance up to 100 m - Smart IR - 4 IR - 5/N Ratio ≥ 55 dB Presets 300 / Tour 8 (up to 32 presets per tour) / Pattern 5 / Scan 50 Alarm I/O : 2/1 - IP66 - Power Supply 12 VDC, 3 A - PoE+ Storage : FTP/ Micro SD card (512 GB)/ NAS</p> <p>STARLIGHT</p>	 <p>220,000,000</p>
<p>93 SD59430U-HNI</p> <p>STARLIGHT</p>	<p>1/3" CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592x1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)</p> <p>STARLIGHT</p>	 <p>350,000,000</p>
<p>94 SD5A432XB-HNR</p> <p>STARLIGHT</p>	<p>NEW</p> <p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+ , H.264+ , H.265 , H.264 , MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.6, 0 Lux (IR on) 4.8 mm–154 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Support human, motor vehicle and non-motor vehicle image capture Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) Support filtering false alarms caused by animals, rustling leaves, bright lights, etc. Pan: 0° to 360° endless , Tilt: -15° to +90°, auto flip 180° , Pan: 0.1°–300°/s , Tilt: 0.1°–200°/s WDR(120), EIS, Defog, RoI,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Alarm I/O : 2/1 , Audio I/O : 1/1 ,PoE+ ,IP67; IK10; TVS 6000 V</p> <p>STARLIGHT Wiz Sense</p>	 <p>440,000,000</p>

ردیف	مدل	مشخصات فني	تصوير	قيمت (ريال)
95	DH-SD5A432GB-HNR	<p>NEW</p> <p>4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS, Max. Resolution 2560 (H) × 1440 (V) Electronic Shutter Speed 1/1 s–1/30,000 s, Min. Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 m(IR), Focal Length 4.8 mm–154 mm Manual Control Speed Pan: 0.1°/s–300°/s, Tilt: 0.1°/s–200°/s Preset 300, Tour 8 (up to 32 presets per tour), Pattern 5, Scan 5 Perimeter Protection, Face Detection, Auto Tracking, Quick Pick, SMD BLC, WDR 120 db, WB, AGC, ANR, Rol, EIS, Defog Electronic, S/N Ratio ≥55 dB Storage : FTP, Micro SD card (512 GB); NAS, Alarm I/O 2/1, Audio I/O 1/1 Power Supply 24 VDC, 2.5 A (± 25%), Operating Temperature –40 °C to +70 °C</p>		460,000,000
96	SD5A432XA-HNR	<p>NEW</p> <p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm–156 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, Rol, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient protection</p>		428,000,000
97	SD5A445XA-HNR	<p>NEW</p> <p>4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on) 3.95 mm–177.7 mm Powerful 45x optical zoom Max. Aperture F1.6–F4.95 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, Rol, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&G&T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection</p>		535,000,000
98	SD6CE445XA-HNR	<p>NEW</p> <p>4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on) 3.95 mm–177.75 mm Powerful 45x optical zoom Max. Aperture F1.6–F4.95 Pan/Tilt Range Pan: 0°–360° endless; Tilt: -20°–90°, auto flip 180° Preset Speed Pan: 300° /s; Tilt: 200° /s WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, Rol, EIS, Defog Deep-learning-based auto tracking and perimeter protection Face detection, SMD Plus, Tripwire, Intrusion. Human/Vehicle/Motor-non Motor Vehicle Detection Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&G&T IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</p>		560,000,000
99	DHI-NVR1104HS-S3/H (V2.0)	<p>NEW</p> <p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity : 1–ch@8MP(30FPS) or 1–ch@5MP(30FPS) or 2–ch@4MP(30FPS) or 2–ch@3MP(30FPS) or 4–ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		27,000,000
100	NVR2104HS-P-1	<p>NEW</p> <p>4 Channel Compact 1U 4PoE WizSense Network Video Recorder, New 4.0 user interface H.264+/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch 1 VGA/1 HDMI simultaneous video output, HDMI 4K, non-simultaneous video output is also supported on 1080p 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images Max. decoding capability: 4×1080P@30fps. Supports adaptive decoding Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Resolution 12M/8M/5M/4M/3M/2M/720P/D1 AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6- channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 4 PoE Ports, 1 SATA port, up to 8 TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1 RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE power supply (10/100 Mbps)</p>		60,000,000
101	NVR2104HS-4KS2	<p>NEW</p> <p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		32,500,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
102	NVR2104HS-P-4KS2	<p>4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support</p>		42,500,000
103	DHI-NVR1108HS-S3/H	<p>NEW</p> <p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live & Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		33,500,000
104	NVR2108HS-4KS2	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		40,000,000
105	NVR2108HS-8P-4KS2	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support</p>		56,500,000
106	NVR2108HS-S3	<p>NEW</p> <p>8 Channel Lite Series, Compact 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding AI by camera: perimeter protection, and SMD Plus Multi-channel Playback Up to 8 channels, HDD Interface 1 SATA port, up to 16 TB Audio Input/Out : 1/1 , Network Port 1 × RJ-45, 10/100 Mbps Power Supply 12 VDC, 1.5 A</p>		43,000,000
107	NVR2108HS-I2	<p>NEW</p> <p>8 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding 1-channel face detection and recognition (AI by NVR) 1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR) AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1 Power Supply 12 VDC, 1.5 A, Operating Temperature -10 °C to +55 °C</p>		58,000,000
108	NVR2108HS-I	<p>NEW</p> <p>8 Channel 12MP WizSense NVR 1/4/8 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled : 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		58,000,000
109	NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		47,000,000
110	DHI-NVR2216-4KS2	<p>NEW</p> <p>16 Channel 4K Lite H.265 NVR 1/4 Live & Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support</p>		62,000,000

111			<p>NEW</p> <p>16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		73,000,000
112			<p>16 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Network Bandwidth: AI off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 Mbps AI on: Access: 72 Mbps; Storage: 72 Mbps; Forward: 36 Mbps Resolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1 Decoding Capability: AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 1 × VGA, 1 × HDMI (simultaneous) 4K Output 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR); AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 1 SATA II port, up to 10TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		72,000,000
113			<p>NEW</p> <p>16 Channel 12MP WizSense NVR 1/4/9/16 Live & Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		90,000,000
114			<p>NEW</p> <p>16 Channel Compact 1U 4K&H.265 Lite Network Video Recorder Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map target classification (human, vehicle) HDMI(4K)/VGA simultaneous video output 1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 port Audio I/O 1/1 for Two Way Talk Only 100 Mbps Network Card, P2P support</p>		69,000,000
115			<p>16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		69,000,000
116			<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p>		90,000,000
117			<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 × front USB2.0, 1 × back USB2.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, 16 Port PoE, ONVIF(profile T/S/G)</p>		151,000,000

ردیف	مدل	مشخصات فني	تصوير	قيمت (ريال)
118	NVR4232-4KS2/L	<p>NEW</p> <p>32 Channel 1U 2HDDs Network Video Recorder Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with attributes, perimeter protection, IVS, people counting, heat map, and SMD, Human & Vehivle Classification 2 SATA III ports, up to 10 TB each port, 1 × front USB2.0; 1 × back USB2.0 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p>		108,000,000
119	NVR4232-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*1000Mbps Network Card, P2P support</p>		108,000,000
120	DHI-NVR5232-4KS2(V2.0)	<p>32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out , P2P Support</p>		179,000,000
121	NVR4432-4KS2/I	<p>NEW</p> <p>32 Channel 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Access, storage or forwarding at 256 Mbps, Max. decoding capability: 10 × 1080p@30 fps Face detection; face recognition; perimeter protection,SMD Plus Multi-channel Playback Up to 16 channel The maximum HDD capacity 4 SATA ports, up to 10 TB Alarm Input 16,Alarm Output 4 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port</p>		195,000,000
122	NVR5432-4KS2(V2.0)	<p>32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support</p>		255,000,000
123	DHI-NVR5464-4KS2(V2.0)	<p>64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support</p>		300,000,000
124	NVR5832-4KS2	<p>32 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10</p>		330,000,000
125	DHI-NVR5864-4KS2(V2.0)	<p>64 Channel 2U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support</p>		440,000,000
126	NVR608-32-4KS2	<p>Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output</p>		375,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
127	NVR608-64-4KS2	<p>Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI/VGA simultaneous video output 8 SATA III ports, up to 10 TB for a single HDD,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output</p>		650,000,000
128	DHI-NVR608-128-4KS2	<p>128 Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA Port Support Raid 0/1/5/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output</p>		760,000,000
129	ESS1508C	<p>2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection</p>		116,000,000
130	PFS3006-4ET-36	<p>6-Port Fast Ethernet Switch with 4-Port PoE 4 PoE ports with 10/100 Mbps Base-TX 2 uplink ports with 10/100Mbps Base-TX Port1-4 ≤30W, whole PoE budget ≤36W Support 802.3af and 802.3at standards OperatingTemperature: -10°C to +55°C Support 250 m long distance PoE transmission Support PoE watchdog Switching Capacity 1.2 Gbps, Packet Forwarding Rate 0.89 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3X ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV</p>		22,500,000
131	PFS3106-4ET-60 (V2.0)	<p>4-Port PoE Switch (Unmanaged) 4 × RJ-45 10/100 Mbps (PoE) 1 × RJ-45 10/100/1000 Mbps (Uplink) 1 × SFP 100/1000 Mbps (Uplink) Intelligent PoE, Hi-PoE 60W (Orange Port), PoE watchdog, 250 m long distance PoE transmission Wide operating temperature: -30°C to +65°C (-22°F to +149°F) Switching Capacity 6.80 Gbps, Packet Forwarding Rate 3.57 Mpps, Packet Buffer Memory 1 Mbit, MAC Table Size 8K Communication Standard IEEE802.3; IEEE802.3u; IEEE802.3X; IEEE 802.3ab; IEEE 802.3z PoE Standard IEEE802.3af; IEEE802.3at; Hi-PoE, 250 m long distance PoE transmission Static Protection Air discharge:15kV Contact discharge:8kV, Thunder-proof Common mode:4kV Differential mode:2kV</p>		41,000,000
132	PFS3010-8ET-65	<p>10-Port Fast Ethernet Switch with 8-Port PoE Port 1-8: 8 × RJ-45 10/100 Mbps (PoE) Port 9-10: uplink with 10/100 Mbps Support 802.3af and 802.3at standards Support 250 m long distance PoE transmission Support PoE watchdog Port1-8 ≤30W, whole PoE budget ≤65W Switching Capacity 2.0 Gbps, Packet Forwarding Rate 1.49 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV</p>		32,150,000
133	PFS3110-8ET-96 (V2.0)	<p>10-Port Unmanaged Desktop Switch with 8 Port PoE Port 1-8: 8 × RJ-45 10/100 Mbps (PoE) Port 9: 1 × RJ-45 10/100/1000 Mbps (uplink) Port 10: 1 × SFP 1000 Mbps (uplink) Communication Standard IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE 802.3ab/IEEE 802.3z PoE Standard IEEE802.3af/ IEEE802.3at/ Hi-PoE/ IEEE802.3bt Port 1-2 ≤ 90 W, Port 3-8 ≤ 30W, totals 96 W Intelligent PoE, BT 90W, Long distance PoE, PoE watchdog, Wide working temperature Lightning Protection Air discharge:8kV Contact discharge:6kV, ESD Protection Common mode:4kV Differential mode:2kV</p>		59,500,000
134	PFS3218-16ET-135	<p>Layer 2 PoE switch 2* 10/100/1000 Base-T (Combo port) 2* 1000 Base-X (Combo port) 16 × RJ45 10/100 Mbps Port 1-2≤60W, Port 3-16≤30W, totals≤135W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Intelligent PoE, PD Alive(PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Switching Capacity 7.2 Gbps, Packet Forwarding Rate 5.3568 Mpps, Packet Buffer Memory 4 Mbit, MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV</p>		102,000,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
135	<p>NEW</p> <p>Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24 × RJ45 10/100Mbps Intelligent PoE, PD Alive(PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Port1/2 support Hi-PoE (60W), PoE+, PoE Port 1-2≤60W, Port 3-24≤30W, totals≤240W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Switching Capacity 8.8Gbps, Packet Forwarding Rate 6.5472 Mpps MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV</p>		131,000,000
136	<p>PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption ≤8W), max transmission distance 300m</p>		6,650,000
137	<p>*1 Channel HDMI Transmission Signal *1080P/1080i/720P/576P/576i/480P/480i Resolution Output Signal , *60M (max)Transmission Distance *Input voltage DCSV *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3</p>		18,700,000
138	<p>Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server, Connection : RS485, RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control, On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB</p>		12,200,000